



z/OS V1R12 JES3 Latest Status and New Features

David Jones
IBM – JES3 Product Team

August 2, 2010
3:00 PM-4:00 PM



SHARE in Boston

Trademarks



The following are trademarks of the International Business Machines Corporation in the United States and/or other countries.

- IBM®
- MVST™
- Redbooks®
- RETAIN®
- z/OS®
- zSeries®

The following are trademarks or registered trademarks of other companies.

- Java and all Java-related trademarks and logos are trademarks of Sun Microsystems, Inc., in the United States and other countries.
- Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.
- Microsoft, Windows and Windows NT are registered trademarks of Microsoft Corporation.
- UNIX is a registered trademark of The Open Group in the United States and other countries.
- SET and Secure Electronic Transaction are trademarks owned by SET Secure Electronic Transaction LLC.

* All other products may be trademarks or registered trademarks of their respective companies.

Notes:

Performance is in Internal Throughput Rate (ITR) ratio based on measurements and projections using standard IBM benchmarks in a controlled environment. The actual throughput that any user will experience will vary depending upon considerations such as the amount of multiprogramming in the user's job stream, the I/O configuration, the storage configuration, and the workload processed. Therefore, no assurance can be given that an individual user will achieve throughput improvements equivalent to the performance ratios stated here.

IBM hardware products are manufactured from new parts, or new and serviceable used parts. Regardless, our warranty terms apply.

All customer examples cited or described in this presentation are presented as illustrations of the manner in which some customers have used IBM products and the results they may have achieved. Actual environmental costs and performance characteristics will vary depending on individual customer configurations and conditions.

This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. Consult your local IBM business contact for information on the product or services available in your area.

All statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility, or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Prices subject to change without notice. Contact your IBM representative or Business Partner for the most current pricing in your geography.

SHARE in Boston

2

Active Releases



Release	FMID	Available	End of Service
z/OS V1R12	HJS7770	September 2010	
z/OS V1R11	HJS7760	September 25, 2009	September 2012 ¹
z/OS V1R10	HJS7750	September 26, 2008	September 2011 ¹
z/OS V1R9	HJS7740	September 28, 2007	September 30, 2010

Notes:

1. Indicates projected date. Actual end of service date has not been announced yet.

Source: http://www-03.ibm.com/systems/z/os/zos/support/zos_eos_dates.html

SHARE in Boston

3

BCP Compatibility



	z/OS V1R9 JES3 HJS7740	z/OS V1R10 JES3 HJS7750	z/OS V1R11 JES3 HJS7760	z/OS V1R12 JES3 HJS7770
z/OS V1R9	Yellow	White	White	White
z/OS V1R10	Yellow	Green	White	White
z/OS V1R11	Yellow	Green	Green	White
z/OS V1R12	White	Green	Green	Green

JES3 code can be compiled and executed on the same or a higher level of the BCP, but never a lower level.

SHARE in Boston

4

JES3 Highlights z/OS V1R10



- APF Alternative
- Request Subsystem Version Information Call enhanced
- Extended Status enhanced
 - New function STATDLST (Data set list)
- Spool Data Set Browse (SDSB)
 - APAR OA24556

See Austin 2009 SHARE Session 2721

SHARE in Boston

5

One of the biggest inhibitors to using the Subsystem Interface has been the fact that SSI calls require running in supervisor state, which in turn requires APF authorization. This means an application coder must go to a system programmer to install the application in an APF library. User written APF programs are a security risk. They could accidentally or maliciously compromise system integrity or step on something that is protected from a normal programs, possibly causing an outage. Even if a user program is risk free, the system programmer must still ascertain that fact when installing an initial version or later versions of that program. An application therefore cannot “code and go”. Having to go through the system programmer makes it take longer to test and debug that application.

Starting in z/OS V1R10 JES3 will support SSIs 11, 75, 79, and 80 in an unauthorized environment – i.e. APF authorization no longer required. In addition, the Subsystem Interface text unit used on dynamic allocation for a SYSOUT data set, DALSSREQ, requires APF authorization. A new text unit, DALUASSR, has been provided for the unauthorized environment.

The Request Subsystem Version Information Call (SSI function code 54) – also known as the “Who-AM-I SSI” - provides a requesting program the ability to obtain version-specific information about a particular subsystem. JES3 updates were made to add the JES3 release running on the JES3 Global, the system name of the JES3 Global, and to indicate if Spool Data Set Browse is supported with the running release of JES3. Additionally, before z/OS V1R10, information strings returned by SSI 54 were built during JES3 initialization. Beginning with z/OS V1R10, the information strings are also built during CONNECT processing. This allows information to be updated when information about the global changes without the local having been restarted. The global information can change in two ways: (1) the global is IPLed and the JES3 release is changed during this IPL, and (2) a Dynamic System Interchange (DSI) is performed, which changes the name of the global and possibly the release. IATUX63, the exit that builds the installation-defined SSI 54 string, is likewise called during CONNECT processing.

A new extended status function STATDLST was added. STATDLST is used to request a data set list for a job. This request obtains verbose type information for all data sets associated with a job. It includes information on SYSIN and other internal data sets.

The need for Spool Data Set Browse (SDSB) is to avoid the single user lock that the SYSOUT Application Programming Interface (SAPI) imposes on applications. Under SAPI, when an application makes a PUT/GET call to access a data set, it causes JES3 to schedule that data set to the requesting application until the application releases the data set. As a result, no other application can access this data set during this time. In addition, SAPI is limited to either output belonging to jobs that have finished running, or output that has been spun off and closed by a job that is still running. SAPI cannot access any other output for an active job, even in completed steps.

SDSB does not have these limitations. Using the SDSB interface an application can use SVC 99 to allocate a SYSOUT data set without going through SAPI to obtain access to it. The benefits are the ability to access output for a job while it is still running and more transparency between the JES3 and JES2.

JES3 Highlights z/OS V1R11

- Enhancements to SPOOL Data Set Browse (SDSB).
- A new way to browse the JES3 managed SYSLOG.
- Additions to SAPI SSI79 and Extended Status SSI80.
- Support for Scheduler Facilities Call SSI70.
- New JES Properties SSI82.
- Enhancements to include a dump of the JES3 global and data spaces for an SVC dump taken while an SSI request (to JES3) is active.

See Seattle 2010 SHARE Session 2350

SHARE in Boston 6

SDSB Enhancement

Active buffers of SYSOUT data sets can now be browsed regardless of which system the data set owner resides on.

SYSLOG Browse

The SYSLOG data sets on a system are logically concatenated into a single logical SYSLOG data set for browse requests.

Additional filtering has been added to SAPI (SSI 79) to select data sets using the job name or job ID associated with a transaction.

The SAPI job ID filter, SSS2JBIL, can now contain generic characters '?' and '*' for use with job ID and transaction job ID filtering.

Additional filtering has been added to Extended Status (SSI 80) to obtain data for terse requests using the job name, job ID, or SYSOUT owner associated with a transaction.

The Extended Status job ID filter, STATJBIL, can now contain generic characters '?' and '*' for use with job ID and transaction job ID filtering.

SSI 70 can be used to retrieve and modify SYSOUT data set characteristics.

SSI 82 provides a common interface for both JES2 and JES3 to return information about multiple JES managed structures. Instead of coding programs that traverse internal structures to retrieve this information, the SSI has packaged the information into a single call.

A user supplied program can call SSI 82 to obtain information about NJE (Network Job Entry) Nodes, SPOOL Volumes, Initiators, JESplex characteristics and Job Classes. The caller specifies a different sub-function value to choose which of the five kinds of information they want the SSI to return.

FIN/SUG APARs

Why?

- Motivation for a FIN (Fixed In Next)
 - Savings in maintenance volume
 - PE reduction due to more regression testing in a release
- Used for
 - Nits
 - Error or unusual paths
 - (Incompatible) functional changes
 - Rarely used for large fixes - SUG is used for these
- Can be rolled back if necessary – FINREVERSAL
 - Rare: Most recent is OA30944. Previous two were done in 2007
- We work with you to make this decision.
- **Please consider them whenever possible!**

SHARE in Boston 7

An APAR is closed FIN or SUG with concurrence from the submitting customer. Closing with FIN means that a fix to this APAR is expected to be delivered from IBM in a release (if any) to be available within the next 24 months. For example, if a customer has a problem in z/OS V1R10 and agrees to a FIN, it does not mean that the problem is or will be fixed in z/OS V1R11 or z/OS V1R12 which are already available.

FIN/SUG APARs



- Included in z/OS V1R10

OA20493	ABEND0C9 in IATMFR5 while processing the 'Job queue length by JES3 function' JMF report
OA20527	Data overlay for a large Sysout file after a re-open
OA21435	Zero line and byte count for DUMPCORE data sets
OA22574	After a warm start with analysis is rejected, JES3 forces analysis on the next start
OA22886	ABEND0C4 in IATDMIT following abend recovery in non-JES3 code

- Included in z/OS V1R11

OA22741	ABEND0C4 in module IATSICA following a configuration change.
OA24930	After termination of JES3 a task fails with ABEND0C4 in module IATSICA.
OA27454	Inquiry issued for a DSN for a job does not complete.
OA26303	ABEND0C4 in module IATDMGR following an ABEND8FB RC25 which was preceded by ABEND8FB RC21.

FIN/SUG APARs



- Included in z/OS V1R12

OA26143	ABEND0C4 in IATUTD2.
OA28818	The text intended for MSGID MSGIAT3828 is issued with MSGID MSGIAT3728 instead.
OA29654	After *S JSS, JES3 does not start all initiators as defined.
OA30005	Removal of CONSTD statement from a JES3 INISH deck has no effect.

Service Highlights Information APARs



APAR	Problem description	Updated
II07968	JES3 Maintenance Philosophy.	11/10/2006
II11768	JES3 Toleration APARs.	7/10/2009
II11784	Recommended JES3 SAPI and Extended Status (SSI 80) maintenance.	7/20/2010
II12051	Known causes of ATL or VTS problems in a JES3 environment.	12/20/2004
II14347	Jobs hung in GMS SELECT state when initiators are defined as JES3 managed.	12/05/2007
II14434	Recommended JES3 TCP/IP/NJE maintenance.	6/11/2010
II14572	Recommended JES3 SPOOL Browse and SYSLOG Browse maintenance.	6/4/2010

- II14572 is new!

Service Highlights Extended Status & SAPI APARs



APAR	Problem description	
II11784	Recommended SAPI and Extended Status (SSI 80) maintenance.	INFO
OA27646	Many simultaneous SDSF jobs are running slow.	HIPER
OA28538	Correct various problems in JES3 HJS7760 (V1R11)	HIPER
OA30764	Selecting an active NJE job in SDSF results in ISF111E dynamic allocation failure.	
OA31199	ABEND9C7 RC04 issued for a request from module IATGRES, FCT ENSTDRV	
OA31512	Extended Status (SSI 80) hang after applying OA27646	PE
OA32853	JES3 stops working : New jobs remain in CI and ended jobs remain in the purge phase.	HIPER

PE = Fixes PTF in Error

APARs closed since 7/1/2009

SHARE in Boston

11

Service Highlights NJE over TCP/IP APARs



APAR	Problem description	
II14434	Recommended JES3 TCP/IP/NJE maintenance.	INFO
OA27522	ABEND0C4 in IATGRQM does not produce a dump.	
OA28145	Missing MSGIAT9141 when using alias in TCP NJE network.	
OA28376	Loop or ABEND0C4 in module IATGRQM.	
OA28421	Missing ENF 58 signals with TCP/IP.	
OA30076	Repetitive ABENDEC8 RC1B NJE transmission loop with damaged jobs.	HIPER
OA30392	The *C TCP,SOCKET= command does not work.	HIPER, PE
OA30781	NETSERV ABENDSEC8 RCB.	
OA31583	TCP FCTs not terminated after DSI with IPL after OA26487.	HIPER, PE
OA32109	The *C TCP,SOCKET= ,I command does not work.	HIPER, PE
OA32601	ABEND0C4 in IATNTTXR when a socket is terminating.	
OA33150	APAR OA31583 did not pre-req PE APAR OA26487.	PE
OA33453	Mark OA30781 PE due to ++HOLD instructions.	PE


PE = Fixes PTF in Error

APARs closed since 7/1/2009

SHARE in Boston

12

OA30076
Added messages for diagnostics



- NJE/TCP transmission stops after MSGIAZ0027I and ABENDEC8 RC1B.
- Difficulty in diagnosing the problem as there was not information about the TCP/NJE selected job.
- APAR adds three messages to post TCP/NJE job information:
 - IAT9384 – Posted by the transmitter at the start of job or sysout transmission. When the transmission is completed then IAT9370 will be posted.
 - IAT9371 – Posted if the transmitter detects an error and the job will be put in hold.
 - IAT9379 – Posted if the receiver detects an error.
- We recommend applying OA30076.

SHARE in Boston 13

OA30076

External symptoms: ABENDEC8 RC=1B issued each time a socket is restarted after message IAZ0027I
NJENSRV S1RZ0 Header/trailer sequence number mismatch

Impact to customer: Unable to transmit data

Analysis: At this time we do not know what was wrong with the data being transmitted.

A TCP/IP NJE receiver node was terminating with SEC8 RC1B but without any information about the job being received and/or transmitted. That is, the receiver issues the IAZ0027I message and takes an abend and keeps on going. This effectively stopped all traffic from sender to receiver and was repeated after the NJE connection was restarted.

From a user point of view an easy way is needed to identify the problem as soon as possible in order to overcome this situation.

This apar has been taken to add diagnostics to assist the customer in determining the cause of the ABENDEC8 and to obtain information the cause of the issue on the sending side.

IAT9384

A specified job or SYSOUT stream has been transmitted to the specified node. When the transmission is completed then IAT9370 will be posted.

IAT9371

A specified job or SYSOUT stream has been transmitted to the specified node. An error occurred before the transmission was completed. The transmitter detected this error and put the job in hold.

IAT9379

A specified job or SYSOUT stream has been partially received from the origin node. The Job header was received, but no Job trailer was received. Since the transmission was incomplete, the data was discarded.

Service Highlights SPOOL and SYSLOG Browse APARs (1 of 2)



APAR	Problem description	
II14572	Recommended JES3 SPOOL Browse and SYSLOG Browse maintenance.	
OA24556	Correct various problems in JES3 HJS7750 SPOOL Browse (V1R10).	SA
OA27646	Many simultaneous SDSF jobs are running slow.	HIPER
OA29534	SYSLOG browse support	HIPER
OA30178	ABEND1FB RC15 or positioning error for SYSLOG browse point	
OA30374	ABEND1FB RC1C RC1D RCDF during SYSLOG browse point processing	
OA30721	Data from other SYSLOG job data sets was being included in the SYSLOG browse.	
OA30764	Selecting an active NJE job in SDSF results in ISF111E dynamic allocation failure.	
OA30842	Incorrect return code RPLFDBK 080304 or 080310 for SYSLOG browse point	
OA30845	ABEND1FB RC80	PE
OA31068	ABEND0C4 in IATDMEB in EBNQ000	HIPER, PE
OA31079	ABEND1FB RC05 attempting SYSLOG I/O	

SA = Special Attention
PE = Fixes PTF in Error

APARs closed since 7/1/2009

SHARE in Boston

14

Service Highlights SPOOL and SYSLOG Browse APARs (2 of 2)



APAR	Problem description	
OA31228	ABEND1FB RCC4 during SPOOL browse I/O	
OA31229	SYSLOG browse loop repeating I/O for same buffer	HIPER
OA31441	ABEND1FB-10 in IATDMEB reported in SDSF after applying OA24556	PE
OA31517	SDSF with JES3 - SJ results incomplete	
OA31971	SDSF LOG S command incomplete	
OA32269	SDSF loop or hang issuing SDSF LOCATE command by time with JES3	HIPER
OA32438	Unable to browse JES3 local's SYSLOG using SDSF LOG command	HIPER
OA32516	ABEND1FB in IATDMEB RC=20 / RC=C4 during SPOOL Browse	PE
OA32781	SDSF JES3: Data access error	PE
OA32946	ABEND1FB RC=20 issued by IATDMFR	PE
OA33040	SDSF browse of a SYSOUT file is missing the last lines.	PE
OA33274	ABEND0C4 in module IATDMEB near label EBT00495	PE

PE = Fixes PTF in Error

APARs closed since 7/1/2009

SHARE in Boston

15

OA24556 & PEs SPOOL Browse



- OA24556 is a significant PTF which corrects various SPOOL Browse problems in HJS7750.
 - Delivered in HJS7750 PTF & in HJS7760 Base and a PTF.
- ALL PEs have minimal impact:
 - OA30845 – Nuisance abend during job termination
 - OA31068 – Nuisance task abend
 - OA31441 – Nuisance task abend
 - OA32516 – SPOOL browse task abend
 - OA32781 – Data access error
 - OA32946 – User exited from SDSF
 - OA33040 – Last lines of an JOBs SYSOUT file is not displayed.
- We recommend applying OA24556!

SHARE in Boston

16

OA30845

External symptoms: ABEND1FB RC=80 issued from IATDMFR

Users affected: All users of HJS7750 and HJS7760 using SDSF

User Impact: This abend is of no impact to the user or system. We are in the process of terminating the address space and doing clean up, attempting to clean up storage that has already been freed.

OA31068

External symptoms: Various externals can be seen for this issue (example in APAR).

Users affected: All users of HJS7750 and HJS7760

User impact: Abending task continues to run. Task is attempting to write to JESMSG LG or JESYSMSG, the control block associated with the locking isn't available, so we are going to branch from IATDMDM to IATDMEB to wait for its availability. As part of the processing a trace entry is going to be written, using the DSBTRACE field; the field is currently zero, we recognize that but then attempt to use its contents. The field is zero because we had just completed spinoff processing. No data is lost. JESMSG LG processing will revert to the JES3 global and cause a significant impact should the application affected be one that does significant message processing. If you don't use spinoff we would recommend applying OA24556.

OA31441

External symptoms: ABEND1FB RC10 under SDSF using spool browse

Users affected: All users of HJS7750 and HJS7760 using SDSF

User Impact: This abend is of minimal impact to the user. The task will abend. We have a timing window where a transient PBUFF shortage can require a redrive of an I/O request using an invalid value.

OA32516

External Symptoms: ABEND1FB in IATDMEB RC=20 / RC-C4 during Spool Browse

Users affected: All users of HJS7750

User Impact: This abend is of minimal impact to the user. The task will abend.

OA32781

External symptoms: Customer attempted to half page scroll through a job's JESJCLIN data set. The JCL for the job contained in-stream SYSIN data sets. A data access error was indicated by SDSF.

Users affected: All users of HJS7750

User Impact: This error is of minimal impact to the user.

OA32946

External symptoms: Under SDSF abend issued (details in APAR).

Users affected: All users of HJS7750, HJS7760 and HJS7770.

User Impact: This abend is of minimal impact to the user. The task will abend.

OA33040

External Symptoms: The last lines of an JOBs SYSOUT file is not displayed.

Users affected: All users of HJS7750, HJS7760 and HJS7770.

User Impact: This error is of minimal impact to the user. The complete SYSOUT file of a JOB is not displayed. If the JOB is copied with XDC, all lines are displayed

Service Highlights Additional JES3 APARs (1 of 3)



APAR	Problem description	
OA27256	ABEND4FB RC28 in IATDMDK because DSSMEME is set to zero.	
OA28093	A JES3 cancel of a TSO LOGON in progress purges the job but the address space does not go away.	
OA28126	JES3DLOG does not collect SYSLOG messages for a LOCAL SYSTEM	HIPER
OA28538	Correct various problems in JES3 HJS7760	HIPER
OA28594	Correct various problems in JES3 HJS7760	SA
OA28689	JES3 line count invalid for null line	
OA28910	ABEND0C4 in IATSSRE followed by ABENDDM747 and ABEND1FB	
OA29050	ABENDDM760 RC=18 following multiple commands for a job	
OA29287	ABEND0C4 in IATSIAD	
OA29417	ABEND0C4 in IATSSCM during DSI processing with JMF active	PE
OA29420	Toleration of JES3 release HJS7760.	HIPER
OA29451	ABEND0C4 in IATSSJI	
OA29547	ABENDDM732 after application of OA27105	HIPER, PE
OA29591	Correct various problems in JES3 HJS7760.	
OA29940	Hang in application under JES3	HIPER

SA = Special Attention
PE = Fixes PTF in Error

APARs closed since 7/1/2009

SHARE in Boston

17

Service Highlights JES3 APARs (2 of 3)



APAR	Problem description	
OA30053	ABEND1FB RC80 IATSIAD	PE
OA30077	IATINII ABEND0C4 if there is a undefined keyword on the CIPARM statement. Not detected by IATUTIS, no warning messages issued.	
OA30129	As of JES3 release HJS7760 the JES3AUX ASID must be defined to your security product or JES3 initialization will hang.	DOC
OA30177	Missing SVC dump from IATDMEB during ABEND1FB	
OA30366	F JES3 issued with CHKX will cause JES3 to stop functioning	HIPER
OA30443	System REXX via AXRCMD with JES3 dumpcore commands may have error returns	
OA30497	In JES3 environment RACF'S z/OS 1.11 enhancement for daily statistics does not function properly	
OA30665	Various DM ABENDs in JES3 during initialization after IOS000I error message	
OA30685	SYSIN data not returned for JESJCLIN SDSB allocated dataset	DOC
OA30841	ABEND0C4 in IATSIAD during point processing using FF02 format	
OA30913	ABENDS052 RC=101 during JES3 DC command with OPTION=DMP	
OA30936	MSGIAT7008 SPLT ERROR DM731 received for SYSOUT file	

PE = Fixes PTF in Error
DOC = Documentation

APARs closed since 7/1/2009

SHARE in Boston

18

Service Highlights JES3 APARs (3 of 3)



APAR	Problem description	
OA30944	ABEND0C4 IATSIAU-SIAUARR IATSICA SVTTVT	
OA31268	Excessive UCBLLOOK processing during dynamic allocation	
OA31776	JES3 MONITOR ISSUES IAT6397 IAT6398 IAT6415 IAT6410 INVALIDLY	
OA31807	ABENDDM137 documentation in JES3 Diagnosis Reference	DOC
OA31855	MSGARC0381A allocation request failed for XXXXX for recall.	HIPER
OA31896	IATGRSP dump followed by ABENDDM747	
OA31962	ABEND0C4 in JES3 module IATMDSB during job termination	
OA32190	ABENDDM672 from IATOSDO for spinoff dataset	
OA32297	MSGIAT8121 issued for MODIFY CANCEL when OSE exists	
OA32301	IAT4133/IAT4174 a reason-text 'SPOOL RECORD ERROR(S)' missing in message manual	DOC
OA32603	ABEND0C4 in IATSICA when AWA addressability attempted	
OA32870	Loop in JES3 module IATSIAF during SSI processing.	HIPER
OA32918	ABEND0C4 in IOSVDEVN issued by SICASTAE	
OA33105	ABEND0C1 in JES3 module IATDMJA following an ABENDDM747.	

PE = Fixes PTF in Error
DOC = Documentation

APARs closed since 7/1/2009

SHARE in Boston

19

OA31268 PTF marked in error



- Excessive UCBLLOOK processing during dynamic allocation.
- **OA33787:** Allocation failure X'484' for non-SMS managed dataset for a job started SUB=MSTR
 - Application started SUB=MSTR which then issues a request jobid so it can use JES3 facilities (in this case dynamic allocation) fails with x'484' for a non-SMS managed dataset.
 - User impact:
 - Dynamic allocations of a non-SMS dataset by an application started SUB=MSTR fails. Non-SMS started under JES3, SMS started under JES3 and SUB=MSTR work.
- If you do not run SUB=MSTR with non-SMS datasets we recommend applying OA31268.
- User's affected:
 - All HJS7760 and HJS7770

SHARE in Boston

20

OA31268

External Symptoms: A job doing multiple allocations is slow and uses excessive CPU Impact to Customer: The job is slow and spends a long time to go through its allocation phase

Service Highlights JESXCF APARs



APAR	Problem description	
OA26664	Support of OA26568.	
OA28128	ABEND0C4 in IXZIXIA when an SRB is being built to respond to an ASID which has been terminated previously.	
OA28878	ABEND0C4 in IXZCNTR over a JES3 restart when RJP consoles are defined.	
OA30415	ABENDS37B during PURGEDQ – Original ABENDA78.	HIPER, PE
OA31944	ABEND0C4 in IXZIXIA when an SRB is being built to respond to an ASID which has been terminated previously.	PE

PE = Fixes PTF in Error

APARs closed since 1/1/2009

SHARE in Boston

21

OA31944 **ABEND0C4 in IXZIXIA....**



- Fixes APAR OA30415 PTFs
- OA30415 PTFs supplied a fix for OA26664 PTFs
 - OA26664 was in support of JES3 OA26568.
 - Applying OA30415 PTFs regressed the fix in OA28128 PTFs.
 - Complicated by JES3 OA27904 fixing defective JES3OA26568.
 - Recommended OA30415 with JES3 OA27904
 - Fix supplied was of greater impact than the fix lost from OA28128.
- Recommend applying OA31944 and JES3 OA27904.
- User's affected:
 - All HJS7730, HJS7740, HJS7750 and HJS7760

SHARE in Boston

22

OA26664

We would not recommend applying OA26664 and JES3 APAR OA26568.
See OA30415 and JES3 APAR OA27904.

OA30415

External symptoms: Customer reported ABEND37B in LOGREC, slip showed original abend was ABENDA78 that was changed to ABEND37B by PURGEDQ.

The PTFs for OA30415 are marked as defective as they regress the fix provided in OA28128.

We recommend applying OA31944 as it provides a fix for a problem introduced by OA26664 and restores the fix supplied by OA28128.

OA31944

External symptoms: ABEND0C4 from module IXZIXIA in JESXCF.

Corrects defective OA30415 PTFs which regressed the fix supplied by OA28128 PTFs.

Affects all users of HJS7730, HJS7740, HJS7750, HJS7760.

We recommend applying OA31944.

We also recommend applying JES3 APAR OA27904 which fixes defective OA26568 PTFs.

JES3 tailored SVC dump exit Adds to an SVC dump



- In R11 JES3 added an SVC dump exit.
 - Created during JES3 initialization and deleted if JES3 ends.
 - The exit was updated with APAR OA29940.
- The exit is designed to conditionally add the JES3, JES3AUX, and JESXCF address spaces to the dump.
 - Added when at least one ASID included in the SVC dump may have a hung subsystem call.
 - JES3 looks for an outstanding SSI request.

SHARE in Boston



23

Beginning with z/OS V1R11, JES3 establishes an SVC dump exit. The SVC dump exit is created during JES3 initialization. The dump exit is new JES3 module IATABTDX which is a dynamic LPA module. The MVS service CSVDYNEX is used to establish the dump exit when JES3 is started. If JES3 is ended, then MVS service CSVDYNEX is used to delete the dump. The delete allows for the dump exit module to be updated when JES3 is started. During initialization, if the call to the MVS service fails and the dump exit cannot be established, initialization will continue and message IAT3207 is written.

Whenever an SVC dump is taken in a user address space, either because it fails, because the operator requests a dump, or because a dump is triggered by a SLIP trap, the JES3 dump exit is called. The dump exit conditionally adds the address spaces for JES3, JES3AUX, and JESXCF to the SVC dump. This occurs if the exit determines that least one ASID, included in the SVC dump, has an outstanding SSI request. Identification of the address spaces with outstanding SSI requests is based upon the same internal activity table counters used to control the setting and resetting of the IAZJSAB activity flags.

JES3 tailored SVC dump exit May create a second dump

- For an SVC dump on the local with a hung subsystem call, the exit will also generate the JES3 *DUMP command.
 - Creates a separate dump of the JES3 global.
 - Will result in ABEND DM137 for the global.
- Due to the dump exit, operators will need to respond to more IAT3714 messages if WANTDUMP=ASK is defined.



SHARE in Boston 24

If the SVC dump originates on a JES3 local, then the JES3 *DUMP command is also generated and a separate dump of the JES3 global is created with ABEND DM137. ABEND DM137 currently indicates that the operator issued the *DUMP command – JES3 Diagnosis Reference. Documentation APAR OA31807 has been created to update the documentation to include that the *DUMP command can be issued for an SVC dump.

Updated JES3 Diagnosis Reference explanation for DM137:

Either the operator issued the *DUMP command or the command was automatically issued from the JES3 Tailored dump exit to supplement a user address space dump. In that case, the dump title will contain the following text: 'COMPON= JES3 DYN DUMP,COMPID=SC1BA,ISSUER=IATABTDX'.

Updated z/OS JES3 Messages description for IAT3833:

Either the operator issued the *DUMP command which caused the CONCMD FCT to be terminated with abend DM137 or the command may have been entered automatically by module IATABTDX to complement a user address space dump. In that case, the dump title will contain the following text: 'COMPON=JES3 DYN DUMP,COMPID=SC1BA,ISSUER=IATABTDX'.

Use WANTDUMP=YES IBM Recommendation

- Provides for more immediate capture of data in the event of a JES3 failure.
- Waiting for an operator to respond to message IAT3714 can result in lost data.
 - System continues processing while the JES3 address space is stopped.
 - System trace records related to the failure may be lost.
- LIMIT and INTERVAL values can be set which force WANTDUMP=ASK should a JES3 failure occur frequently.

SHARE in Boston 25

Specifies that a dump should be taken immediately when a JES3 failure occurs.

WANTDUMP is a parameter of the OPTIONS initialization statement.

Default is WANTDUMP=YES,LIMIT=3,INTERVAL=10 (INTERVAL is in minutes)

Commands allow the WANTDUMP option to be changed including the LIMIT and INTERVAL specifications.

IBM suggests that you allow the WANTDUMP option on the STANDARDS initialization parameter to default to "YES" instead of setting it to "ASK". Using the default of "YES" allows the system to determine what action to take when a JES3 failure condition occurs. In today's sysplex environment setting this parameter to "ASK" can cause delays in operations because the JES3 address space essentially stops functioning until you respond to the IAT3714 message. Also, certain portions of the dump, such as the system trace, are invalid because the system continues processing until you response to message IAT3714.

Service Recommendation Use SMP/E



- Important when JES3 and the BCP are installed in different zones.
 - Often done to separate product maintenance streams.
 - Consider when using SDSF.
 - See z/OS Planning for Installation.
 - JESXCF, DFSMS, Netserv/TCPIP and allocation services are all part of the BCP!
- Can use REPORT CROSSZONE commands and manually check the information.
- Strongly recommend using SMP/E automatic cross-zone requisite checking.

SHARE in Boston

26

The SMP/E REPORT command helps you obtain information about SYSMODs installed on your system. REPORT CROSSZONE is used to list conditional requisites that must be installed in certain zones because of SYSMODs installed in other zones. This information can help you synchronize service for related products that are in different zones like JES3 and JESXCF. You can use separate REPORT CROSSZONE commands and closely review the output -- very manual and prone to mistakes. We strongly recommend using the SMP/E automatic cross-zone requisite checking.

Creating a cross-zone set is documented in the z/OS Program Directory:

7.3.1 Create a Cross-Zone Set



There are different methods that can be used for cross-zone processing. A zone group can be defined and added to the install jobs or the XZGROUP operand can be used. XZGROUP(value) contains a list of ZONESETs or zones that are used to establish the zone group. Each value in the list must be a valid ZONESET or zone name. XZGROUP(value) would be added to the install jobs instead of adding the XZREQCHK operand to one or more ZONESETs.

In OS/390 Release 3, SMP/E introduced the operand, XZREQ, which provides a method for a user to more easily install cross-zone requisites. SMP/E identifies the cross-zone requisites needed in the set-to zone by reading CIFREQ data in the secondary zones of the zone group in effect for the current APPLY/ACCEPT commands. Any CIFREQ data that is for FMIDs installed or being installed in the set-to zone that are not yet in the set-to zone causes the required SYSMODs to become candidates for installation. If the FORFMID operand is also used, the FMID specified on the CIFREQ must match one of the FMIDs specified on the FORFMID operand for the SYSMOD to become a candidate.

By adding the XZREQ operand, the CIFREQ SYSMODs are installed automatically into the set-to zone. However, XZREQ does not install the CIFREQs in the other cross-dependent zones. An APPLY XZREQ needs to be performed against the other zones in order to synchronize service.

Note: If SYSMODs being installed into the set-to zone have requirements against the other cross-zones, that service must be APPLY'd to those zones before installation can be completed into the set-to zone.

SHARE JES3 Requirements

SHARE #	IBM FITS #	Title	State
SSJES3032645	MR0203033521	JES3 Dynamic Spool enhancement – Accepted for SPOOL Add function	Accepted
SSJES3032645	MR0615106131	JES3 Dynamic Spool enhancement – Created for SPOOL Remove/Delete function	Recognized
SOJES393353	MR1020084625	JES3 - Dataset Integrity for JES3's Datasets	Recognized
SSJES399351	MR041400724	Provide access to SPOOL utilization data	Recognized
SSJES397305	MR1020084630	JES3 - OUTDISP support of OUTPUT JCL statement	Recognized
SSSHARE011776	MR1020084632	Perform DFHSM 'RECALL' for Batch Jobs Before They Are Active	Recognized
SSJES3032649	MR0210035755	Provide a Way to Know Which JES3 Jobs Use a Spool Extent	Recognized
SSSHARE01633	MR1020084712	JES3 Dump Job (DJ) support for dumping jobs by spool dataset	Recognized
SBJES383304	MR1020084616	JES3 Job Scheduling With HSM.	Recognized
SBJES379323	MR1020084614	JES3 - Inquiry for Job Reserving a Device	Recognized

SHARE in Boston
27


80 requirements from SHARE were added to the IBM requirements database on 10/19/2008!

Survey question 1



- What release level?
 - z/OS V1R12 –
 - z/OS V1R11 –
 - z/OS V1R10 –
 - z/OS V1R9 –
 - z/OS V1R8 –

Survey question 2



- NJE users?
 - Using BSC?
 - Using SNA?
 - Using TCP/IP?

- Anyone using RJP?
 - Using BSC?
 - Using SNA?

- Anyone using BDT for file-to-file transfer?

SHARE in Boston 29

Results from Seattle SHARE:

NJE users? **8** – 18 in attendance

Using BSC? **1**

Using SNA? **6** – some working to convert to TCP/IP

Using TCP/IP? **6**

Anyone using RJP? **3**

Using BSC? **0**

Using SNA? **3**

Anyone using BDT for file-to-file transfer? **4**



z/OS V1R12 JES3

SHARE in Boston

30

z/OS V1R12 JES3 Agenda



- Enable ENF58 signaling with SAPI SSI79.
- New JES Device Information Services SSI83.
- JES3 Extended Address Volume (EAV) support.

SHARE in Boston

31

ENF58 signaling Overview



- Event Notification signal 58 (ENF58) is issued by JES3 for various SYSOUT data set changes.
 - Listeners of ENF58 are informed of changes such as data set being selected or deleted or changes to the job containing the data set.
 - Limited to the signal being issued only for data sets that have been allocated using the DALRTCTK text unit.
- JES3 extends ENF58 support so SAPI users can request the broadcast of signals for any SYSOUT data sets.
 - This allows users to monitor status changes during the lifetime of SYSOUT any data set.

ENF58 signaling Usage notes



- New SAPI SSI79 disposition flag SSS2RENF (IAZSSS2) to request ENF58 signals using PUTGET (SSS2PUGE).
- New Extended Status SSI80 output field STVS1ENF (IAZSSST) indicates when ENF58 signaling is enabled for a SYSOUT data set.
- Listeners should monitor and take appropriate action based on the ENF58 subtype.
 - See *z/OS JES Application Programming* for ENF58 details.

SHARE in Boston

33

See *z/OS MVS Programming: Authorized Assembler Services Guide* for information about how to use the ENFREQ macro to listen to these events.

See *z/OS JES Application Programming* for additional ENF58 details.

SSI83 – JES Device Information Services



- Allow an application program to obtain information on devices managed by JES such as printers, readers, etc.
- Implementation will be staged over several releases due to the large number of device types supported by JES.
- With V1R12:
 - JES3 returns information for local printer devices.
 - JES2 returns information for both local and remote printer devices.

SSI83 Information returned



- Local printer attributes:
 - JDCXPREF = Common prefix section
 - JDPHPRPU = Printer data header
 - JDPCPRPU = Printer common section
 - JDPWRKSL = Printer work selection section
 - JDPFPRT = Non-impact printer section (FSS printers)
 - JDP3PRPU = Printer JES3 section (JES3 specific attributes)
- Jobs that are currently active on the devices:
 - JDJBINFO = Current job information section
 - JDUTINFO = Current output information section
 - JDU3INFO = Current output information JES3 section
- System in the JESplex on which each device is located:
 - JDSIHDR = System information header

SHARE in Boston

35

SSI83 Usage notes



- SSI83 Calls made using IEFSSREQ with SSOBFUNC = 83.
- SSOBINDV points to the parameter lists mapped by IAZSSJD.
- SSJDFREQ is set to obtain the data or release the storage.
- Returned information is returned in storage buffers chained to the parameter list.
- The storage buffers are accumulated across multiple calls and must be explicitly released via a storage release request.
- Not available in V1R12 JES3:
 - Extensive filtering capabilities that allow application program to subset device information.
 - Support to return device data in 64-bit addressable virtual storage.
 - Plan to make available in a future release.

JES3 EAV support



- DFSMS has added basic and large format sequential data sets to the list of Extended Address Space (EAS) eligible data sets.
- JES3 EAV support allows SPOOL, checkpoint, and Job Control Table (JCT) data sets to be anywhere on an EAV.
- Provides customers the ability to have SPOOL data sets larger than 65,520 cylinders (982,800 tracks).

SHARE in Boston

37

With z/OS V1R10 and higher releases, z/OS has added support for DASD volumes having more than 65,520 cylinders. To expand the capacity of DASD storage volumes beyond 65,520 cylinders, z/OS had to extend the track address format. Hence the name **Extended Address Volume (EAV)** for a volume of more than 65,520 cylinders.

EAVs provide increased z/OS addressable disk storage. EAVs help to relieve storage constraints as well as simplify storage management by providing the ability to manage fewer, large volumes as opposed to many small volumes.

With z/OS V1R12, DFSMS added support for base and large format sequential data sets that now can be exploited for JES3 data sets.

An added benefit is that large sequential data sets, DSNTYPE=LARGE, when EAS eligible on an EAV, are no longer limited to the volume size of 65,520 cylinders. This allows JES3 customers to have much larger SPOOL data sets.

- Each SPOOL data set must be contained in a single extent. (A single extent is one adjoining group of tracks or cylinders.)
- You cannot allocate any secondary extents.
- You cannot allocate more than 1024 spool data sets.

JES3 EAV support Usage notes



- To make a data set EAS eligible, specify the EATTR=OPT keyword on the JCL DD statement used to create the data set.
 - See speaker notes for sample JCL.
- The JES3 JCT Utility (IATUTJCT) can be used to migrate the existing JCT and checkpoint data sets to EAS eligible data sets.
- Existing facilities and procedures for managing SPOOL data sets can be used to add an EAS eligible data set or replace an existing SPOOL data set with an EAS-eligible data set.

SHARE in Boston

38

EATTR is used to control whether a data set can have extended attribute DSCBs and thus control whether it can be allocated in EAS.

- EATTR of NO indicates that the data set can not have extended attributes or reside in EAS. This is the default for non-VSAM data sets such as basic and large format sequential data sets.
- EATTR of OPT indicates that the data set can have extended attributes and can optionally reside in EAS.

In order to allow a JCT data set to be copied without a cold start, JES3 provides a program called the JCT utility, or IATUTJCT. This utility can be used to migrate existing JCT and checkpoint data sets to EAS eligible data sets.


Managing the JES3 SPOOL space does not change with the support added to exploit EAVs. See chapter 6 of the *z/OS JES3 Initialization and Tuning Guide* for details on adding and replacing SPOOL data sets.

Example JCL to allocate then format a JES3 spool extent in EAS on an EAV:

```
//ALLOC EXEC PGM=IEFBRI4
//SPXTNT DD DSN=SYS1.JESPACE,DISP=(NEW,KEEP,KEEP),
// UNIT=3390,VOL=SER=J3SPL1,
// DCB=(RECFM=U,BLKSIZE=2048),
// SPACE=(CYL,80000),EATTR=OPT,
// DSNTYPE=LARGE
//SPLFRMT EXEC PGM=IEBDG
//SPXTNT DD DSN=SYS1.JESPACE,DISP=SHR,
// UNIT=3390,VOL=SER=J3SPL1,
// DCB=(RECFM=U,BLKSIZE=2048,BUFNO=255),
// DSNTYPE=LARGE
//SYSPRINT DD SYSOUT=*
//SYSIN DD *
DSD OUTPUT=(SPXTNT)
FD NAME=SPOOL,FILL=X'FF',LENGTH=4084
CREATE NAME=(SPOOL),QUANTITY=2147483647
END
```

JES3 EAV support

Changes for 28-bit cylinder values



- EAV support has extended cylinder values to 28-bits.
- Additional changes made include:
 - BADTRACK support:
 - BADTRACK initialization statement
 - *MODIFY,Q command
 - Messages updated:

• IAT1140	• IAT4034
• IAT1141	• IAT4035
• IAT1145	• IAT6363
• IAT1146	• IAT8539



SHARE in Boston 39

The BADTRACK initialization statement is used to identify defective tracks on a spool volume. The *MODIFY,Q command can be used to add a BADTRACK element for a defective track in a spool data set. Both the initialization statement and command have been updated to allow one- to seven-digit hexadecimal values for the cylinder specification.

Messages which include a cylinder value have been updated to output seven-digit hexadecimal values.

JES3 EAV support

More changes for 28-bit cylinder values



- More updates made for 28-bit cylinder values:
 - Job Validation SNAP Output.
 - JES3 Monitoring Facility (JMF) reports updated for SPOOL information:
 - SPOOL DATA SET DESCRIPTION
 - SINGLE TRACK TABLE SPACE ALLOCATION SNAPSHOT
 - JES Properties (SSI 82) SPOOL Volume Information
 - SDSF SPOOL (SP) panel



SHARE in Boston 40

Additional externals which include or return cylinder values have been updated for 28-bit values including:

- The Spool Record Validation (SRV) entries for the Job Validation SNAP Output.
- JES3 Monitoring Facility (JMF) reports for SPOOL Information
- JES Properties subsystem interface (SSI 82) for SPOOL Volume Information.
- SDSF SPOOL (SP) panel.

JES3 EAV support

Other JES3 data sets


SHARE
Technology - Connections - Results

- Other JES3 data sets, which are physical sequential data sets, may also reside anywhere on an EAV.
 - Data sets include, but are not limited to:
 - JES3IN
 - JES3ABEND
 - JES3DRDS
 - JES3SNAP
 - SYSABEND
 - SYSUDUMP
 - PROCLIBs
 - User data sets

SHARE in Boston 41

Other JES3 data sets are accessed using standard DFSMS access methods – versus EXCP for SPOOL, checkpoint, and JCT data sets. Based upon DFSMS support for the data set type, these data sets may also reside anywhere on an EAV.

JES3 EAV support Migration & Coexistence considerations



- A SPOOL extent, checkpoint, or JCT data set with extended attributes in the EAS cannot be opened on earlier-level systems.
 - The JES3 global and all locals must be at z/OS V1R12 with z/OS V1R12 JES3.
 - For earlier-levels of z/OS and JES3, JES3 initialization fails with system completion code 313 accompanied by system message IEC144I and return code 0C.
 - For z/OS V1R12, earlier-level JES3 initialization fails with system completion code 113 accompanied by system message IEC142I and return code 44.
 - Both messages identify the data set that could not be opened.
 - See speaker notes for examples.

SHARE in Boston

42

Care must be taken when specifying EATTR=OPT for data sets that are not EAS-eligible in z/OS V1R10 or z/OS V1R11 – basic and large format sequential data sets. These will not be allowed to be opened from z/OS V1R10 or z/OS V1R11 if they were allocated in z/OS V1R12 with extended attributes.

- Example message:

IEC144I 313-0C,IFG0194D,JES3,JES3,CHKPNT,0340,DJEAV ,SYS1.CMSCKPT1

IEC144I - Explanation: The error occurred during processing of an OPEN macro instruction for a data set on a direct access device.

0C = During an attempt to open a data set, open encountered an extended attribute DSCB (format-8) for a data set that is not eligible to have extents above 65,520 cylinders. This is invalid for this type of data set.

Care must be taken when specifying EATTR=OPT for JES3 data sets that cannot be opened with z/OS V1R10 and z/OS V1R11 JES3 (even if z/OS V1R12 is IPLed). These JES3 releases cannot open data sets if they were allocated in z/OS V1R12 with extended attributes.

- Example message:

IEC142I 113-44,IFG0194D,JES3,JES3,SPOOL1,0340,DJEAV ,SYS1.CMSPOOL1

IEC142I - Explanation: The error occurred during processing of an OPEN macro instruction or an OPEN macro instruction with a TYPE=J operand.


44 = An attempt was made to open an EAS eligible data set on a volume with more than 65,520 cylinders but the DCBE flag, DCBEEADSCBOK, indicating that the caller understands extended attribute (Format 8/9) DSCBs was not set.

JES3 Education



- Use SHARE!
 - z/OS Basics: JES3 for New Users
 - Next session right here!
 - Past proceedings.
 - JES3 Basics: Introduction to JES3 Parts 1 & 2
Denver 2009 sessions 2351 & 2352 – Greg Thompson
 - Let us know what you want to know!

JES3 Education



- IBM Training: ITSO zSeries JES3 Workshop
 - **5 day class starting 9/13/2010 – Chicago, IL**
 - Search the Education catalog for 'ITS80'
 - http://www-03.ibm.com/services/learning/ites.wss/us/en?pageType=course_description&courseCode=ITS80

- IBM Education Assistant JES3 modules
 - [z/OS V1.8 JES3 Networking TCP/IP NJE](#)
 - [z/OS V1R10 JES3 ease of use, application enablement, spool browse](#)

SHARE in Boston 44

http://www-03.ibm.com/services/learning/ites.wss/us/en?pageType=course_description&courseCode=ITS80

ITS80 description:

This course covers the design, installation, and management of a JES3 system, both externally and internally. All features and functions of JES3 will be discussed. Coverage includes the functions and features of all releases currently available, including the current release z/OS JES3 V1.9.

References

ABCs of z/OS System Programming



- Volume 1 – [SG24-6981](#) – published April 2008 (JCL/SDSF)
- Volume 2 – [SG24-6982](#) – published September 2008 (Job mgmt)
- Volume 3 – [SG24-6983](#) – published August 2007
- Volume 4 – [SG24-6984](#) – not available yet
- Volume 5 – [SG24-6985](#) – published February 2008
- Volume 6 – [SG24-6986](#) – published August 2008
- Volume 7 – [SG24-6987](#) – published October 2008
- Volume 8 – [SG24-6988](#) – published May 2007
- Volume 9 – [SG24-6989](#) – published January 2008
- Volume 10 – [SG24-6990](#) – published September 2008
- Volume 11 – [SG24-6327](#) – published November 2005
- Volume 13 – [SG24-7717](#) – published June 2009 (JES3)

Source: www.redbooks.ibm.com/cgi-bin/searchsite.cgi?query=abcs

SHARE in Boston

45

- Volume 1 – SG24-6981 (<http://www.redbooks.ibm.com/abstracts/sg246981.html>)
- Volume 2 – SG24-6982 (<http://www.redbooks.ibm.com/abstracts/sg246982.html>)
- Volume 3 – SG24-6983 (<http://www.redbooks.ibm.com/abstracts/sg246983.html>)
- Volume 5 – SG24-6985 (<http://www.redbooks.ibm.com/abstracts/sg246985.html>)
- Volume 6 – SG24-6986 (<http://www.redbooks.ibm.com/abstracts/sg246986.html>)
- Volume 7 – SG24-6987 (<http://www.redbooks.ibm.com/abstracts/sg246987.html>)
- Volume 8 – SG24-6988 (<http://www.redbooks.ibm.com/abstracts/sg246988.html>)
- Volume 9 – SG24-6989 (<http://www.redbooks.ibm.com/abstracts/sg246989.html>)
- Volume 10 – SG24-6990 (<http://www.redbooks.ibm.com/abstracts/sg246990.html>)
- Volume 11 – SG24-6327 (<http://www.redbooks.ibm.com/abstracts/sg246327.html>)
- Volume 13 – SG24-7717 (<http://www.redbooks.ibm.com/abstracts/sg247717.html>)

References

Internet Discussion Group



- Subscribe to JES3-L@LISTSERV.UGA.EDU
- To subscribe mail to LISTSERV@LISTSERV.UGA.EDU with no subject and the body containing the command:
 - SUBSCRIBE JES3-L *your name*
- To post, mail to JES3-L@LISTSERV.UGA.EDU

Source: www.lsoft.com/scripts/wl.exe?SL1=JES3-L&H=LISTSERV.UGA.EDU

SHARE in Boston

46

<http://www.lsoft.com/scripts/wl.exe?SL1=JES3-L&H=LISTSERV.UGA.EDU>

Wrap up!



Questions?

Discussion?

Thank You!

SHARE in Boston

47


Appendix



- SYSPROG Tools
 - JES3 Monitoring
 - Autostart for JSS
 - Display a Spool Record
 - Dynamic LPA Facility
 - JES3 Auto-Restart

SYSPROG Tools

JES3 Monitoring



- Provides automatic monitoring of JES3 functions on the global and local processors and also in the CI FSS address spaces.
- Pay attention to its messages: IAT6395,IAT6396,IAT6397
 - Operators may not recognize a new message or may react inappropriately causing an outage.
 - Consider them for your Automation to highlight them to your operator.
- JES3 monitoring may save you an outage!

SHARE in Boston 49

JES3 provides automatic monitoring of JES3 functions on the global and local processors and also in the CI FSS address spaces. Two types of monitors are used:

JES3 loop and wait monitor


The JES3 loop and wait monitor ensures the two main JES3 tasks, the Nuc and the Aux task, are not suspended or in an infinite loop. When that happens, no other JES3 function (called FCTs) can be dispatched besides the currently active one. JES3 periodically examines the status of those two functions and informs the operator, through WTOR IAT6410, about the condition. MODIFY JES3 commands can be used to change the Monitoring interval and threshold for the loop and wait monitor.

JES3 monitor DSP

The monitor DSP runs as an FCT under the JES3 Nuc task. It monitors unavailable JES3 resource. A JES3 resource is anything that can use an FCT or a job that can become unavailable. The monitor DSP also monitors resources that a job is waiting for (data set allocation requests and tape mounts).

SYSPROG Tools

JES3 Monitoring – Check Please!



- **MODIFY JES3,CHK**
- Allows the operator to check the “health” of the JES3 address space.
 - Local, global, or CI FSS
- A summary report issued to the console lists any exception conditions found.
- CHK may save you an outage!
- Works in IPCS as well for a JES3 dump.
 - ip verbx jes3 'option=chk'
 - Does not work well for a dump from another address space!

SHARE in Boston 50


A complement to both monitors is an exception analysis function. This function is invoked by an operator MVS command while JES3 is running or offline during dump analysis. The function provides a summary report of unusual conditions as defined by JES3. Analysis can be requested for the local, global, or CI FSS address spaces. This function will be enhanced and fine-tuned over time as more and more checks are implemented.

The command runs asynchronously to the JES3 address space code. Therefore, it is possible that JES3 is changing the data while the command is executing. This can lead to an occasional program check or a loop while the command is executing. When a loop is detected, message "IAT6417 Command 'CHK' exceeded 1 minute. Reply 'CANCEL' to stop" is issued and a response is required. In either case, enter the command again.

The same function can be invoked in IPCS and Dump Core (DC).

For z/OS JES V1.8 and earlier, make sure you have OA15913 applied.

SYSPROG Tools **JES3 Monitoring – Check Please!**



- Categories of exception conditions checked are:
 - CI and MDS
 - FCTs and DSPs
 - General
 - JSS and Job queue
 - Spool

SHARE in Boston 51

There are various types of exception analysis, each of which is called in turn by IATABEA. Each one is contained in its own module. Over time more checks may be added based on your and our experience.

SYSPROG Tools **JES3 Monitoring – Check Please!**



- Some of the more interesting exception conditions are:
 - PROCLIB update is disabled
 - LOCATE subtask has abended
 - Job queue is held
 - FAILDSP pending for an FCT
 - IATXARQ issued for JESMSG processing
 - There are unprocessed WTDs (i.e. commands) on the Work-to-do queue
 - There are WEVs on one or more WLM queue
 - Main has been flushed
 - WLM reclassification is in progress
 - One or more priorities has been held
 - Threshold percent of job numbers in use
 - Marginal/minimal spool condition
 - Minimal JSAM buffer condition

SHARE in Boston

52

There are too many exception conditions to list. The ones listed here are probably among the more interesting or likely to be seen by you, the customer.

SYSPROG Tools **Autostart for JSS**



- Autostart can be used to make JES3 functions available after JES3 initialization without requiring the *S,JSS command.
- Add PARM=NOREQ to the start command
 - S JES3,PARM=NOREQ
- Modify the JES3 Cataloged Start Procedure
 - //IEFPROC EXEC PGM=IATINTK,DPRTY=(15,15),PARM=NOREQ
 - Can nullify on the start command: S JES3,PARM=

SHARE in Boston

53

PARM=NOREQ specifies that JES3 global will start JES automatically if you want JES3 functions to be available after JES3 initialization without requiring the *S,JSS command. Place this in the JES3 start procedure. This avoids having operators forget to do the *S JSS command when restarting JES3. To nullify the parameter you can specify S JES3,PARM= on the start command.

SYSPROG Tools **Display a Spool Record**



- Dump core DSP can be used to display the contents of a spool record that has a spool address of *mmmm.rrrrrrr*
 - ***S DC,SPADDR=mmmm.rrrrrrr**
 - The *mmmm* portion of the spool address is the spool extent number (module) where the record resides.
 - The *rrrrrrr* portion of the spool address is the spool record number within the spool extent.
 - The spool address must be coded exactly as shown; leading zeros in either part of the spool address must be specified.
- When the contents of the spool record are displayed, only the non-zero portion at the end of the record is displayed.

SHARE in Boston

54

The dump core DSP is used to display and modify data in main storage, to intercept program flow during execution, and to format control blocks for debugging. This facility can be used only on the global processor.

SPADDR=mmmm.rrrrrrr

Displays the contents of the spool record that has a spool address of *mmmm.rrrrrrr*. The *mmmm* portion of the spool address is the spool extent number (module) where the record resides. The *rrrrrrr* portion of the spool address is the spool record number within the spool extent. The spool address must be coded exactly as shown; leading zeros in either part of the spool address must be specified.

When the contents of the spool record are displayed, only the non-zero portion at the end of the record is displayed. For example, if a particular spool record contains only zeros after the first 100 bytes of the records, only the first 100 bytes of the record will be displayed.

In order to use SPADDR, you must specify KEY=SYSTEM when calling dump core:

```
*CALL DC,OUT=CON,KEY=SYSTEM
```

See the *z/OS JES3 Commands* document for more details on using dump core.

SYSPROG Tools **Display a Spool Record Examples**



```
*CALL,DC,OUT=CON,KEY=SYSTEM  
IAT6306 JOB09992 IS DC, CALLED BY CN 01  
IAT7921 ISSUE START/CANCEL/RESTART DC REQUEST
```

```
*S,DC,SPADDR=0003.00000384  
SPOOL RECORD: 0003.00000384  
00000000-00030000 03840000 C3E2C240 00000000 *.....D..CSB ....*  
00000010-00000000 00000000 5CA2A3A3 0012D6E4 *.....*stt..OU*  
00000020-E37EC3D6 D540D2C5 E87EE2E8 E2E3C5D4 *T=CON KEY=SYSTEM*
```

```
*S,DC,SPADDR=0002.000012A8  
SPOOL RECORD: 0002.000012A8  
00000000-00020000 12A80001 D6E2C540 00000000 *.....y..OSE ....*  
00000010-00000000 00000000 5CA2A3A3 00600060 *.....*stt.-.-*  
00000020-00000000 00000000 00000000 00000000 *.....*  
00000030-00000000 00000000 00000000 00000000 *.....*  
00000040-00000000 00000000 00000000 00000000 *.....*  
00000050-00000000 00000000 00000000 00000000 *.....*  
00000060-FFFFFFFF *.....*
```

SHARE in Boston

55

SYSPROG Tools **Dynamic LPA Facility**



- APARs with restart type DynLPA can be activated without an IPL.
- New versions of JES3 LPA modules can be dynamically added to LPA by issuing the following commands:
 - **F LLA,REFRESH**
 - **SETPROG LPA,ADD,MODNAME=modname,DSN=LNKLST**
 - Message CSV551I confirms the LPA add.
- Perform a hot start of local start of JES3 to activate the changed module.
 - No IPL required!
 - Message IAT3085 confirms the changed module.

SHARE in Boston

56

APARs eligible for refresh with the dynamic LPA facility will be marked in the APAR closure text.

- Type/IPL (Local,DynLPA)
- Type/IPL (Global,DynLPA)
- Type/IPL (Rolling,DynLPA)

See Info APAR II07968 – JES3 Maintenance Philosophy

The SETPROG command can be issued while JES3 is active. The change does not take effect until JES3 is restarted. This allows you to back out the change if necessary.


If the fix must be installed on more than one system, a SETPROG command must be issued for each system. Multiple modules can be added at one time using MODNAME=(*modname*,...,*modname*)

When the required modules have been added to LPA, perform a hot start or local start of JES3 (without an IPL of the system) to activate the change. During initialization, JES3 picks up the new versions of the modules and issues message IAT3085. On the JES3 global processor, the message appears in JES3OUT only. On the JES3 local processors, the message appears on the console.

Monitor CSA usage. Dynamic add of modules to the LPA reduce the CSA space available as older versions of the module are not removed.

SYSPROG Tools

Dynamic LPA Facility Example



- Build a new copy of all the library directory indexes:
`MODIFY LLA,REFRESH`
- Use SETPROG to add updated module IATSICA to the LPA:
`SETPROG LPA,ADD,MODNAME=IATSICA,DSN=LNKLST`
`CSV551I 10.16.14 LPA ADD 868`
`SUCCESSFUL: 1 UNSUCCESSFUL: 0 NOT PROCESSED: 0`

MODULE	RESULT
IATSICA	SUCCESSFUL
- CSV551I confirms the add was successful.
- Perform a hot or local start to activate the changed module.
- IAT3085 identifies the changed modules:
`IAT3085 LPA MODULES CHANGED: IATSICA ...`

SHARE in Boston57

The APAR ++hold data will contain instructions. An example is:

New versions of JES3 LPA modules can be dynamically added to LPA by issuing the following commands:

```
F LLA,REFRESH          followed by:
SETPROG LPA,ADD,MODNAME=IATSICA,DSN=LNKLST
```

SYSPROG Tools **JES3 Auto-Restart**



- JES3 will auto-restart if a critical DSP or FCT terminates.
 - CRITICAL=YES is added to the DSP/FCT definition.
 - DSPs/FCTs defined as critical include:
 - JSAM
 - WTDDRVR (I/O bound Inquiry/Modify)
 - MSGC (JDS access, Started Task init., Main Connect, etc.)
 - JSS
 - MAIN
 - ENSTDRV (Extended Status)
- JES3 will auto-restart for repetitive and consecutive failures.
- IAT3098 identifies the reason for the auto-restart.

SHARE in Boston

58

Auto-restart logic previously existed for a configuration change. Auto-restart means detaching the IATNUC task and reattaching it. It's like doing a DSI without changing the global.

The parameter CRITICAL=YES is added to the DSP or FCT definition in the DSP directory.

Refer to the z/OS JES3 Customization document:

- IATYDSD (Generate a DSP Dictionary Entry)
- IATYFCD (Generate Function Control Table)

IAT3098 text identifies if JES3 is restarting due to a CONFIGURATION CHANGE, a CRITICAL FCT ABEND, or REPETITIVE FAILURES.



End of slides.

SHARE in Boston

59