


IBM Americas, ATS, Washington Systems Center

ICSF Update Share 11487 Anaheim, CA August 2012

Greg Boyd (boydg@us.ibm.com)





Agenda

HCR7790

- -Dynamic PKA Master Key Change
- -Coordinated KDS Administration
- -KDS Related Changes
- -Suite B
- TKE 7.1
- HCR7770
- HCR7780

Page 2

- Toleration and Migration
- VM and Linux

Share 11487 ICSF Update





Dynamic RSA-MK Change

Prior to HCR7790 or without CEX3 on z196/z114	HCR7790 with CEX3 on z196/z114
Generate key parts and calculate checksums	Generate key parts and calculate checksums
Disable PKA Services	
Load the RSA-MK parts (and autoswitch)	Load the RSA-MK parts
Reencipher the PKDS under the new master key	Reencipher the PKDS under the new master key
Activate the PKDS	Change the RSA-MK and activate the PKDS
Enable PKA Services	
Enable PKA read, write, create and delete access	
Change the ICSF Options data set to point to the new PKDS	Change the ICSF Options data set to point to the new PKDS



Coordinated KDS Administration: Coordinated CKDS Master Key Change and Coordinated CKDS Refresh

- Simplified process for performing ICSF CKDS administration in both a single system environment and more importantly in a sysplex environment.
- In a sysplex environment coordinated CKDS refreshes and coordinated CKDS change-mk operations are driven from a single ICSF instance across the sysplex.
- CKDS sysplex communication protocol level 2 provides better sysplex communication performance, uses less overhead, and is more serviceable then the prior release sysplex communication protocol.



ICSF Master Key Management

CSFMKM10 ------ ICSF – Master Key management ------

OPTION ===>

Enter the number of the desired option.

- 1 INIT / REFRESH / UPDATE CKDS Initialize a Cryptographic Key Data Set or activate an updated Cryptographic Key Data Set
- 2 SET MK

- -- Set a master key (AES, DES, ECC)
- 3 REENCIPHER CKDS -- Reencipher the CKDS prior to changing a symmetric master key
- 4 CHANGE SYM MK -- Change a symmetric master key and activate the reenciphered CKDS
- 5 INIT/REFRESH/UPDATE PKDS -- Initialize a Public Key Data Set or activate an updated Public Key Data Set or update the Public Key Data set header
- 6 REENCIPHER PKDS -- Reencipher the PKDS
- 7 CHANGE ASYM MK -- Change an asymmetric master key and activate the reenciphered PKDS
- 8 COORDINATED KDS REFERESH Perform a coordinated KDS refresh
- 9 COORDINATED KDS CHANGE MK Perform a coordinated KDS change master key

Press ENTER to go to the selected option.

Press END to exit the previous menu.



Select the KDS to Refresh

CSFCRC4P ------ ICSF - Coordinated Refresh KDS Selection ------

Select one Key Data Set type and press ENTER to continue.

==> / CKDS - Cryptographic Key Data Set

_	-		-
		1000	
		-	

Coordinated KDS Refresh

CSFCRC10 ------ ICSF – Coordinated KDS Refresh ------COMMAND ===> To perform a coordinated KDS refresh to a new KDS, enter the KDS names below and optionally select the rename option. To perform a coordinated KDS refresh of the active KDS, simply press enter without entering anything on this panel. CKDS KDS Type ===> Active KDS ===> 'PLEX.TEST.CKDS' New KDS ===> Rename Active to Archived and New to Active (Y/N) ===> N Archived KDS ===> Press ENTER to perform a coordinated KDS refresh.

Press END to exit to the previous menu.

_	-	

© 2012 IBM Corporation

ICSF Master Key Management

Share 11487 ICSF Update

Page 8

CSFMKM10ICSF – Master Key management
OPTION ===>
Enter the number of the desired option.
1 INIT / REFRESH / UPDATE CKDS – Initialize a Cryptographic Key Data Set or activate
an updated Cryptographic Key Data Set
2 SET MK Set a master key (AES, DES, ECC)
3 REENCIPHER CKDS Reencipher the CKDS prior to changing a symmetric master key
4 CHANGE SYM MK Change a symmetric master key and activate the reenciphered CKDS
5 INIT/REFRESH/UPDATE PKDS Initialize a Public Key Data Set or activate an updated Public Key Data Set or update the Public Key Data
set header
6 REENCIPHER PKDS Reencipher the PKDS
7 CHANGE ASYM MK Change an asymmetric master key and activate the reenciphered PKDS
8 COORDINATED KDS REFERESH – Perform a coordinated KDS refresh
9 COORDINATED KDS CHANGE MK – Perform a coordinated KDS change master key
Press ENTER to go to the selected option.
Press END to exit the previous menu.



Select the KDS for the MK Change

CSFCRC4P ------ ICSF - Coordinated Refresh KDS Selection ------

Select one Key Data Set type and press ENTER to continue.

==> / CKDS - Cryptographic Key Data Set

Page 9



Coordinated KDS Change MK

CSFCRC20 ------ ICSF – Coordinated KDS change master key ------ COMMAND ===>

To perform a coordinated KDS change master key, enter the KDS names below and optionally select the rename option.

KDS Type ===> CKDS

```
Active KDS ===> 'PLEX.TEST.CKDS'
```

New KDS ===>

Rename Active to Archived and New to Active (Y/N) ===> N

Archived KDS ===>

Create a backup of the reenciphered KDS (Y/N) ===> N Backup KDS ===>

Press ENTER to perform a coordinated KDS refresh. Press END to exit to the previous menu.



Related Changes

New API – CSFCRC/CSFCRC6

Coordinated KDS Admin can be invoked for your own application, via a new API

New messages

CSFCM624I ICSF Communication Level Changed

CSFC0316 Reencipher Fail ... for entry ckdslabel

New healthcheck

ICSF_COPROCESSOR_STATE_NEGCHANGE

- ACTIVE -> STOPPED
- ACTIVE -> ONLINE
- ACTIVE -> OFFLINE
- DEACTIVATED -> STOPPED

Serial

_	_	
	_	
	_	

Coprocessor Management Panel

Select the coprocessors to be processed and press ENTER.

Action characters are: A, D, E, K, R and S. See the help panel for details.

CoProcessor	Number	Status	AES	DES	ECC	RSA
G01	0000001	ONLINE	υ	U	C	υ
G02	00000002	ACTIVE	A	U	А	Е
G03	0000003	ACTIVE	A	υ	А	C
E04	0000004	ACTIVE	A	U	-	C
Н05		ACTIVE				

See TechDoc Flash10749 'Activation of Cryptographic Coprocessors and Cryptographic Algorithms with ICSF, HCR7780'



Other Enhancements

- Additional ECC functionality
 - -ECC-DH

-AES KEK for wrapping ECC private keys

- Expanded AES key support
 - -AES KEK

-Variable length AES keys (HMAC support)

 Enhanced ANSI TR-31 interoperable secure key exchange



Other Enhancements

PIN Block Decimalization support

0123456789 ABCDEF

0123456789012345



- PKA RSA Optimal Asymmetric Encryption Padding (OAEP) with SHA-256 Algorithm
- Accelerator support for 2048 thru 4096-bit keys

Page 14



Suite B

- Symmetric Encryption
 - -AES w/key sizes of 128 and 256
- Digital Signatures




- -ECDSA Elliptic Curve, Digital Signature Algorithm
- Key Agreement
 - -ECDH Elliptic Curve, Diffie-Hellman
- Message Digest
 - -SHA-2 (SHA-256 and SHA-384)

http://www.nsa.gov/ia/programs/suiteb_cryptography/



TKE – Trusted Key Entry Workstation





TKE 7.0 – New hardware platform

- TKE 7.0 will run on a new hardware platform
 - -4765 (CEX3) Crypto Card
 - -Add USB ports; Drop serial ports
 - Old Kobil Smart Card readers used a serial port
 - New Omnikey Smart Card readers use the USB
 - Support USB Flash Memory Drive (as an alternative to the DVDRAM media)
 - -New Smart Cards
 - JCOP41 NXP Smart Cards replacing the older Data Key Smart Cards
 - Six digit PINs





TKE 7.0 - New Key Support

Support ECC Master Keys

-32-byte AES Key to protect ECC Keys

-Generation and loading of ECC keys not supported on TKE 7.0

CBC Key Wrapping

-KW-ENH Key Wrapping Enhanced

-KW-ORIG Key Wrapping Original





TKE - Migration Wizard

TKE 6.0 introduced a configuration migration utility to automate the process of replacing a host crypto adapter

- -Captured public configuration data
 - -Roles
 - -Authorities
 - Domain Control Settings
 - Only 'public' (non-secret data), no key material

TKE 7.0 adds support for migration of key material

- -Master Keys only
- -New Smart Card Types
 - Migration CA (MCA)
 - Injection Authority (IA)
 - Key Part Holder (KPH)






TKE 7.1

- AES operational key support
- Single process for loading an entire key
- Single process for generating multiple key parts
- Use of ECDH to exchange encrypted key material with a CEX3
- New access control points
- Migrate roles utility
- Support for more key parts on a smart card
- Host cryptographic module support
- Display of active IDs on the TKE console



HCR7770 – Protected Key

MSA-3 (Message Security Assist 3)





Protected Key – How it works

- Create a key, with the value 'ABCD' and store it as a secure key in the CKDS (i.e. encrypted under the Master Key, MK)
 - -E_{MK}(x'ABCD') => x'4A!2' written to the CKDS and stored with a label of MYKEY
- Execute CSNBSYE (the clear key API to encrypt data), but pass it the key label of our secure key, MYKEY; and text to be encrypted of 'MY MSG'

```
-CALL CSNBSYE(....,
MYKEY,
'MY MSG '....)
```

Page 22



Protected Key – How it works (cont ...)

- ICSF will read MYKEY from the CKDS and pass the key value x'4A!2' to the CEX3
- Inside the CEX3, recover the original key value and then wrap it using the wrapping key
 - -D_{MK}(x' 4A!2') => x' ABCD'
 - -E_{WK}(x'ABCD') => x'*94E'
- ICSF will pass the wrapped key value of x'*94E' to the CPACF, along with the message to be encrypted
- In the CPACF, we'll retrieve the wrapping key, WK
 - -D_{wk}(x'*94E') => x'ABCD'
 - $-E_{x'ABCD'}$ ('MY MSG ') => ciphertext of x'81FF18019717D183'



Key Store Policy

- By defining a policy, a security administrator can make symmetric and asymmetric keys more secure, without requiring application changes
 - Key Token Authorization Checking

CSF.kds.TOKEN.CHECK.LABEL.action

Default Key Label Checking

CSF.kds.TOKEN.CHECK.DEFAULT.LABEL

Duplicate Key Token Checking

CSF.kds.TOKEN.NODUPLICATES

- Granular Key Label Access Control

CSF.CSFKEYS.AUTHORITY.LEVELS.action

Symmetric Key Label Export Control

CSF.XCSFKEY.ENABLE.keytype

- PKA Key Management Extensions control
 - CSF.PKAEXTNS.ENABLE(.WARNONLY)



HCR7770 – ECC Support

Effective Key Size Security

Symmetric RSA Key ECC Key

Key Size	Size	Size
80	1024	163
112	2048	224
128	3072	256
192	7680	384

256 15360 512 From NIST SP 800-57 Part 1 (Table 2) at www.nist.gov

Elliptic Curve Support

-ECDSA

-New ECC Master Key




Image from DeviceForge and other sites



ICSF – HCR7780

FIPS Mode SPE (OA32012/UA55967) for PKCS #11 – Public Key Cryptographic Token Interface

- PKCS #11 provides APIs for talking to devices which hold crypto info or perform crypto operations (think Smart Cards)
- -FIPSMODE was an option in HCR7770
- -SPE provides additional support required for FIPS certification

CKDS Constraint Relief

- -CKT, in-storage copy of CKDS, above the bar
- -Optimized for speeding up searches (binary tree)
- -Limit performance impact of bulk updates
 - -Buffering Read-Aheads
 - -Tighten allocate / open / IO / close / deallocate process





FIPS-198 Keyed HMAC Support (OA33260)

- New algorithm FIPS-198
- New Key/Token
 - -Variable-length key token
- Variable Length CKDS (LRECL 1024)
 - -Fixed- and variable-length records
 - -Conversion Utility CSFCNV2
- New callable services
 - -Key Management
 - -HMAC Generate and Verify





ICSF Versions supported on z196/z114

ICSF FMIDs

-HCR7790 (www.ibm.com/systems/z/os/zos/downloads)

-HCR7780 (z/OS V1.13)

-HCR7770 (z/OS V1.12)

-HCR7751 (z/OS V1.11)



-HCR7750 (z/OS V1.10 with IBM Lifecycle Extension)

-HCR7740 (z/OS V1.9 with IBM Lifecycle Extension with PTFs)

Page 28



Crypto Express3 Support

Crypto Express3 Toleration APARs

–ICSF	OA29839

- -RMF OA28670
- -SAF OA29194
- -RACF OA29193





ICSF Toleration

HCR7780 - Toleration APAR OA33320

-CBC Key Wrapping - 'Enhanced' key wrapping

-ECDSA Keys in the PKDS


HCR7780 - HMAC Toleration Support OA34402

 Old versions of ICSF (HCR7750, HCR7751, HCR77770) will ignore XCF messages with a longer format coming from HCR7780 systems

HCR7790 - Variable Length AES OA36718

-HCR7780 can tolerate the new AES keys

See SMPE Support for ICSF FIXCAT ICSF790C/K



Page 30

Share 11487 ICSF Update

August 8, 2012

© 2012 IBM Corporation



Breaking News (kind of)

 OA37278/UK63842 – IBM Ported Tools for z/OS: OpenSSH V1R2 support for crypto hardware

-Requires HCR7770

-http://www.ibm.com/systems/z/os/zos/features/unix/ported/

Page 31



z/VM 5.4 and z/VM 6.1

 Provides guest support, VM does not directly use the crypto hardware

-Crypto Express3 - VM64656

-Protected Key Support - VM64793



Page 32

	_	
_		
=		

Linux on System z

- CPACF
 - -CCA 4.2 support is now available



-Some MSA-4 support is available, some will be available manure distribution

CEX3

- Drivers in SUSE SLES11 SP1/SLES12 and RedHat RHEL 6.0 provide exploitation support for the CEX3
- Drivers in SUSE SLES10 SP3 and SLES11 and Red Hat RHEL 5.4 provide toleration support (CEX3 acts like a CEX2)
- CCA (secure key support) software download at the CryptoCards website (http://www.ibm.com/security/cryptocards/?S_TACT=107AG01W&S_C MP=campaign)



Summary

 z196 and z114 continues the implementation and support of new crypto technology, techniques and standards to support the evolving world of data security





Session #11487 Feedback





References

IBM Pubs

- ICSF Overview, SA22-7519
- ICSF Administrator's Guide, SA22-7521
- ICSF Application Programmer's Guide, SA22-7522
- ICSF System Programmer's Guide, SA22-7520

TechDocs

www.ibm.com/support/techdocs

and search on 'crypto'



Trademarks

The following are trademarks of the International Business Machines Corporation in the United States and/or other countries.

AlphaBlox*	GDPS*	RACF*	Tivoli*
APPN*	HiperSockets	Redbooks*	Tivoli Storage Manager
CICS*	HyperSwap	Resource Link	TotalStorage*
CICS/VSE*	IBM*	RETAIN*	VSE/ESA
Cool Blue	IBM eServer	REXX	VTAM*
DB2*	IBM logo*	RMF	WebSphere*
DFSMS	IMS	S/390*	zEnterprise
DFSMShsm	Language Environment*	Scalable Architecture for Financial Reporting	xSeries*
DFSMSrmm	Lotus*	Sysplex Timer*	z9*
DirMaint	Large System Performance Reference [™] (LSPR [™])	Systems Director Active Energy Manager	z10
DRDA*	Multiprise*	System/370	z10 BC
DS6000	MVS	System p*	z10 EC
DS8000	OMEGAMON*	System Storage	z/Architecture*
ECKD	Parallel Sysplex*	System x*	z/OS*
ESCON*	Performance Toolkit for VM	System z	z/VM*
FICON*	PowerPC*	System z9*	z/VSE
FlashCopy*	PR/SM	System z10	zSeries*
* Registered trademarks of IBM Corporation	Processor Resource/Systems Manager		

The following are trademarks or registered trademarks of other companies.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries. Cell Broadband Engine is a trademark of Sony Computer Entertainment, Inc. in the United States, other countries, or both and is used under license therefrom.

Java and all Java-based trademarks are trademarks of Sun Microsystems, Inc. in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

ITIL is a registered trademark, and a registered community trademark of the Office of Government Commerce, and is registered in the U.S. Patent and Trademark Office.

IT Infrastructure Library is a registered trademark of the Central Computer and Telecommunications Agency, which is now part of the Office of Government Commerce.

* All other products may be trademarks or registered trademarks of their respective companies.

Notes:

Performance is in Internal Throughput Rate (ITR) ratio based on measurements and projections using standard IBM benchmarks in a controlled environment. The actual throughput that any user will experience will vary depending upon considerations such as the amount of multiprogramming in the user's job stream, the I/O configuration, the storage configuration, and the workload processed. Therefore, no assurance can be given that an individual user will achieve throughput improvements equivalent to the performance ratios stated here. IBM hardware products are manufactured from new parts, or new and serviceable used parts. Regardless, our warranty terms apply.

All customer examples cited or described in this presentation are presented as illustrations of the manner in which some customers have used IBM products and the results they may have achieved. Actual environmental costs and performance characteristics will vary depending on individual customer configurations and conditions.

This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. Consult your local IBM business contact for information on the product or services available in your area.

All statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility, or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products. Prices subject to change without notice. Contact your IBM representative or Business Partner for the most current pricing in your geography.