




SHARE – Boston, Aug. 12, 2013 – Session 13350

CICS Performance Health Checks

By Ivan Gelb



Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Trademarks & Copyright

- The following are trade or service marks of the IBM Corporation: CICS, CICSplex, DB2, IBM, z/OS, Parallel Sysplex. Any omissions are purely unintended.

© 2013, Ivan L. Gelb

Gelb Information Systems Corp.

10 Country Club Lane, Marlboro, NJ 07746-1447

Phone: 732-303-1333 E-mail: ivan@gelbis.com

Permission granted to reproduce presentation only in its entirety and include all copyright notices. All comments, contributions and questions are welcomed and rewarded.

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Disclaimer


All of the information in this document is tried and true. However, this fact alone cannot guarantee that you can get the same results at your workplace. In fact, some of this advice can be hurtful if it is misused and misunderstood. Gelb Information Systems Corporation, Ivan Gelb and anyone found anywhere assume no responsibility for this information's accuracy, completeness or suitability for any purpose. Anyone attempting to adapt these techniques to their own environments anywhere do so completely at their own risk. 😊 😊





Agenda

- Your Questions @Anytime
- Analysis Overview
- Processor Performance
- I/O Performance



Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Analysis Pre-Req

- Service level goals or agreements
- Biorhythms (peaks and valleys) of the entire system
- Biorhythms of the critical applications
- History of all service level failures





Recommended Health Indicators

- **System Saturation Design Point** at 80% of total CPU capacity – What is your SDP?
- Importance 1, the top business critical applications at less than 80% of total physical processor utilization
- CICS QR TCB utilization at less than 70% of one physical CPU
- Demand paging rate of $< 5/\text{second}/\text{critical workload}$





Analysis - 1

Top 5 benefits of health checks:

1. Meet or exceed Service Level Agreements.
2. Manage and control costs.
3. Assure scalability of business systems.
4. Insure that computer resources are aligned with the business priorities.
5. Reduce computer resource requirements.





Analysis - 2

Top 5 performance health check activities:

1. Insure that PR/SM and Workload Manager (WLM) Service Policy provide proper priority for processor access.
2. Verify that and CICS QR TCB is degraded by less than 50%
3. Insure adequate supply of real and virtual storage
4. Review Temporary Storage and Transient Data
5. Review logical and physical file activity





Analysis - 3

Critical Success Factors:

- Document service level requirements
- Collect short and long term performance data
- Customize all system components (z/OS, CICS, MQ, DB2,...) to maintain and protect performance of business critical applications
- Coordinate performance management and capacity management activities so they are symbiotic functions





Analysis - 4

Performance Hierarchy


CICS dispatching and tuning; resource usage
Tools: SMF 110 records, statistics

TCB/thread execution priority and contention
Tools: RMF Workload Activity Reports

MVS dispatching and tuning; SRM/WLM
Tools: RMF Reports, SMF Type 30 records

LPAR Mgmt (weights and fair share)
Tools: RMF CPU and Partition data reports

CPU cycles - Engines, Memory, Devices, Hardware configuration
Tools: RMF



Source: Threadsafe Considerations for CICS, SG24-6351

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Measurement Data Sources

- **Resource Measurement Facility (RMF)**
 - System wide resource level details: CPU disks, storage, workload performance, and summary
- **System Management Facility (SMF)**
 - Address space level details for: batch, STC, CICS, etc. + resource level details/address space
 - VSAM file and DB2 object level activity details
- **CICS end-of-day and interval statistics**
 - CICS Region level statistics and resource counters for: CPU, IO, storage, transactions, connections, etc...
- **CICS Monitoring Facility (CMF)**
 - Transaction level details. All the details!





Processor Utilization Governors

- **Three** dispatchers involved in making physical processor time available to a CICS task:
 - PR/SM dispatches ready tasks of LPARs
 - LPAR weights based shares are enforced by PR/SM only when the processor is at or near 100% busy or LPAR is capped
 - z/OS dispatches tasks within LPAR,
 - z/OS Workload Manager (WLM) Service Policy governs which tasks get highest dispatching priority based on a workload's importance
 - CICS dispatches tasks within each CICS region
 - CICS' Dispatcher handles tasks in their specified priority order while being possibly constrained by various performance and capacity control parameters





CEC Level Processor Analysis

- LPAR weight and the guaranteed CPU share

LPAR	Weight	% Share	Guaranteed # of CPs
PRODHOT1	225	45%	7.2
PRODHOT2	225	45%	7.2
PRODWARM	50	10%	1.6
Totals	500	100%	16

- Effective Dispatch Time from PR/SM view
- Partition Dispatch Time from z/OS view
- **Short CPUs** = task only gets a **fraction** of one CP





RMF Partition Data Report

PARTITION DATA REPORT														PAGE					
z/OS V1R10				SYSTEM ID S59				DATE 07/28/2009				INTERVAL 15.00.010							
				RPT VERSION V1R10 RMF				TIME 17.00.00				CYCLE 1.000 SECONDS							
MVS PARTITION NAME				S59				NUMBER OF PHYSICAL PROCESSORS				26				GROUP NAME		N/A	
IMAGE CAPACITY				1127				CP				20				LIMIT		N/A	
NUMBER OF CONFIGURED PARTITIONS				12				AAP				2							
WAIT COMPLETION				NO				IFL				0							
DISPATCH INTERVAL				DYNAMIC				ICF				2							
								IIP				2							
----- PARTITION DATA -----														-- LOGICAL PARTITION PROCESSOR DATA --		-- AVERAGE PROCESSOR UTILIZATION PERCENTAGES --			
-----MSU-----							-CAPPING-		PROCESSOR-		----DISPATCH TIME DATA----				LOGICAL PROCESSORS		--- PHYSICAL PROCESSORS ---		
NAME	S	WGT	DEF	ACT	DEF	WLM%	NUM	TYPE	EFFECTIVE	TOTAL	EFFECTIVE	TOTAL	LPAR MGMT	EFFECTIVE	TOTAL				
S59	A	801	0	502	NO	0.0	20.0	CP	02.13.34.022	02.13.34.604	44.52	44.53	0.00	44.52	44.53				
S50	A	500	0	0	NO	0.0	20.0	CP	00.00.00.000	00.00.00.000	0.00	0.00	0.00	0.00	0.00				
S51	A	100	0	53	NO	0.0	3.0	CP	00.13.58.918	00.14.00.016	31.07	31.11	0.01	4.66	4.67				
S55	A	101	0	68	NO	0.0	20.0	CP	00.18.01.114	00.18.01.538	6.01	6.01	0.00	6.01	6.01				
S58	A	999	0	493	NO	0.0	20.0	CP	02.11.06.315	02.11.06.763	43.70	43.70	0.00	43.70	43.70				
+PHYSICAL+										00.00.04.264		0.02		0.02					
TOTAL										04.56.40.370		04.56.47.186		0.04		98.89 98.93			
S59	A	150					2	AAP	00.00.00.373	00.00.00.419	0.02	0.02	0.00	0.02	0.02				
S50	A	150					2	AAP	00.00.00.000	00.00.00.000	0.00	0.00	0.00	0.00	0.00				
S51	A	150					2	AAP	00.00.00.737	00.00.00.770	0.04	0.04	0.00	0.04	0.04				
S55	A	150					2	AAP	00.00.00.283	00.00.00.327	0.02	0.02	0.00	0.02	0.02				
S58	A	150					2	AAP	00.00.00.317	00.00.00.359	0.02	0.02	0.00	0.02	0.02				
+PHYSICAL+										00.00.00.993		0.06		0.06					
TOTAL										00.00.01.713		00.00.02.870		0.06		0.10 0.16			

Source: RMF V1R10 Report Analysis

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



RMF Monitor III Processor Delays - 1

RMF V1R8 Processor Delays

Line 1 of 138
Scroll ==> HALF

Command ==>

Samples: 60 System: MVS1 Date: 10/31/06 Time: 09.10.00 Range: 60 Sec

Jobname	CX	Service Class	CPU Type	DLY %	USG %	EApp1 %	Holding Job(s)					
							%	Name	%	Name	%	Name
WSWS7	O	OMVS	CP	11	46	59.4	9	*ENCLAVE	7	DBS3DIST	7	WSP1S2F
WSP1S2FS	SO	WASCR	CP	4	4	42.5	2	DBS3DIST	2	WSWS7	2	VTAM44
			AAP	6	0	98.4	6	*ENCLAVE				
WSP1S6FS	SO	WASCR	CP	0	0	5.3						
			AAP	6	0	7.7	6	*ENCLAVE				
DBS3DBM1	S	DB2HIGH	CP	2	6	0.8	2	XCFAS	2	DBS3DIST	2	WSP1S2F
WSP1S6F	SO	WASCR	CP	0	2	1.9						
			AAP	2	2	0.7	2	*ENCLAVE				
U078069	O	OMVS	CP	2	4	1.2	2	WSWS7	2	DBS3DIST	2	U078069
WSP1S4F	SO	WASCR	CP	0	0	0.1						
			AAP	2	0	0.4	2	WSP1S6F				
U078068	O	OMVS	CP	2	0	0.2	2	XCFAS	2	WSWS7	2	*ENCLAVE
DBS3DIST	SO	DB2HIGH	CP	0	78	111.0						
			IIP	0	2	21.3						
XCFAS	S	SYSTEM	CP	0	28	24.1						

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



RMF Workload Activity

WORKLOAD ACTIVITY

PAGE 1

z/OS V1R10

SYSPLX SVPLX3
RPT VERSION V1R10 RMF

DATE 07/28/2009
TIME 12.00.00

INTERVAL 14.59.995 MODE = GOAL

POLICY ACTIVATION DATE/TIME 11/01/2007 10.12.11
- WORKLOAD & SERVICE CLASS PERIODS -

----- SERVICE CLASS(ES)

REPORT BY: POLICY=BASEPOL WORKLOAD=STC_WLD SERVICE CLASS=STCHIGH RESOURCE GROUP=*NONE
CRITICAL =NONE
DESCRIPTION =High priority for STC workloads

-TRANSACTIONS-		TRANS-TIME	HHH.MM.SS.TTT	--DASD I/O--	--- <th>SERVICE TIME</th> <th>--- <th>--PROMOTED--</th> <th>---- </th></th>	SERVICE TIME	--- <th>--PROMOTED--</th> <th>---- </th>	--PROMOTED--	----
AVG	0.00	ACTUAL	62	SSCHRT 0.0	IOC 0	CPU 0.000	CP 0.00	BLK 0.000	AVG 695.77
MPL	0.00	EXECUTION	62	RESP 0.0	CPU 0	SRB 0.015	AAPCP 0.00	ENQ 0.000	TOTAL 1.49
ENDED	62	QUEUED	0	CONN 0.0	MSO 0	RCT 0.009	IIPCP 0.00	CRM 0.000	SHARED 0.00
END/S	0.03	R/S AFFIN	0	DISC 0.0	SRB 2933	IIT 0.000			
#SWAPS	62	INELIGIBLE	0	Q+PEND 0.0	TOT 2933	HST 0.000	AAP 0.00		
EXCTD	0	CONVERSION	0	IOSQ 0.0	/SEC 2	AAP 0.000	IIP 0.00		
AVG ENC	0.00	STD DEV	482			IIP 0.000			
REM ENC	0.00				ABSRPTN 759				
MS ENC	0.00				TRX SERV 757				

-PAGE-IN RATES-	
SINGLE	0.0
BLOCK	0.0
SHARED	0.0
HSP	0.0

PER IMPORTANCE	PERF INDX	--TRANSACTIONS--		-----RESPONSE TIME-----			-EX VEL%	TOTAL	-EXE--
		-NUMBER-	-%-	-----GOAL-----	---ACTUAL---	TOTAL	GOAL ACT	USING%	DELAY%
1 1	0.5	62	100	00.00.00.500	80% 98.4%	98.4%	0.0	0.0	0.0
2 2	N/A	0	0	00.00.05.000	80% 0.0%		N/A	0.0	0.0
3 3	N/A	0	0	00.00.15.000	AVG 00.00.00.000		N/A	0.0	0.0

TOTAL 62 100

REPORT BY: POLICY=BASEPOL WORKLOAD=STC_WLD SERVICE CLASS=STCLOW RESOURCE GROUP=*NONE
CRITICAL =NONE
DESCRIPTION =Low priority for STC workloads

-TRANSACTIONS-		TRANS-TIME	HHH.MM.SS.TTT	--DASD I/O--	--- <th>SERVICE TIME</th> <th>--- <th>--PROMOTED--</th> <th>---- </th></th>	SERVICE TIME	--- <th>--PROMOTED--</th> <th>---- </th>	--PROMOTED--	----
AVG	0.12	ACTUAL	5.341	SSCHRT 0.1	IOC 250903	CPU 14.636	CP 0.82	BLK 0.000	AVG 679.09
MPL	0.12	EXECUTION	5.341	RESP 2.7	CPU 2046K	SRB 0.032	AAPCP 0.00	ENQ 0.000	TOTAL 81.44

Source: RMF V1R10 Report Analysis

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Notes- RMF Workload Activity

CP Percentage of CPU time used by transactions running on standard CPs in the service or report class period.

The calculation is:

$$\text{APPL\% CP} = \frac{\text{CPU} + \text{SRB} + \text{RCT} + \text{IIT} + \text{HST} - \text{AAP} - \text{IIP}}{\text{Interval length}} * 100$$

Notes:

1. The interval length in a sysplex is the common interval length.
2. The AAP and IIP times may be normalized from a faster zAAP or zIIP.

AAPCP

Percentage of CPU time used by zAAP eligible transactions running on standard CPs. This is a subset of APPL% CP.

IIPCP Percentage of CPU time used by zIIP eligible transactions running on standard CPs. This is a subset of APPL% CP.

AAP Percentage of CPU time used by transactions executed on zAAPs in the service or report class period.

IIP Percentage of CPU time used by transactions executed on zIIPs in the service or report class period.

Source: RMF V1R10 Report Analysis

Think *Faster* with
Gelb Information



AAPCP and IIPCP will forecast ZAAP and ZIIP potential utilization with PROJECTCPU option specified in IEAOPT member of PARMLIB

© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



RMF Workload Activity

REPORT BY: POLICY=BASEPOL WORKLOAD=CICS_WLD SERVICE CLASS=CICSLow RESOURCE GROUP=*NONE PERIOD=1 IMPORTANCE=4
 CRITICAL =NONE

-TRANSACTIONS-		TRANS-TIME	HHH.MM.SS.TTT
AVG	0.00	ACTUAL	0
MPL	0.00	EXECUTION	0
ENDED	893	QUEUED	0
END/S	0.50	R/S AFFIN	0
#SWAPS	0	INELIGIBLE	0
EXCTD	0	CONVERSION	0
AVG ENC	0.00	STD DEV	0
REM ENC	0.00		
MS ENC	0.00		

SUB	P	RESP TIME (%)	STATE SAMPLES BREAKDOWN (%)					-----STATE-----			
			--ACTIVE--	READY	IDLE	-----WAITING FOR-----		SWITCHED	SAMPL (%)		
TYPE			SUB	APPL		MISC	TIME	LOCAL	SYSPL	REMO	
CICS	BTE	0.0	0.0	0.0	0.0	6.7	88.9	4.4	0.0	0.0	0.0
CICS	EXE	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

GOAL: RESPONSE TIME 000.00.30.000 FOR 75%

SYSTEM	RESPONSE TIME ACTUAL%	EX VEL%	PERF INDX
*ALL	100	N/A	0.5
CB8B	100	N/A	0.5
CB86	100	N/A	0.5
CB87	100	N/A	0.5
CB88	100	N/A	0.5
CB89	100	N/A	0.5

-----RESPONSE TIME DISTRIBUTION-----				
----	----	----	----	----
TIME	NUMBER OF TRANSACTIONS	PERCENT		
HH.MM.SS.TTT	CUM TOTAL	CUM TOTAL	IN BUCKET	IN BUCKET
< 00.00.15.000	893	100	893	100
<= 00.00.18.000	893	100	0	0.0
<= 00.00.21.000	893	100	0	0.0

Save CPU time and money! Get the Goal and Response time Distribution from RMF. No CICS transaction level data collection required to get this!

Source: RMF V1R10 Report Analysis

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



CICS Statistics

- Data written to SMF files
- Control via:
CEMT SET STATISTICS
INTERVAL(hhmmss) **default = 3 hrs.**
ENDOFDAY(hhmmss) **default = 000000**
- Can be requested via CEMT for any one of the over 20 specific areas of CICS
- Reports via DFHSTUP and DFH0STAT





CICS Statistics - 2

- **Recommendation for detailed health check analysis:**

INTERVAL(hhmmss) Make the interval **match** the RMF – SMF data collection interval's duration.

Same use as DFHSIT STATINT.

- Enables most effective analysis of resource utilization statistics collected by SMF- RMF in conjunction with the CICS statistics.





CICS Dispatcher Domain -1

- Statistics to watch:
 - Current MXT limit
 - ☠ Nr. Of Times MXT reached
 - Peak tasks??
 - TRANCLASS limit by class
 - ☠ TRANCLASS limit reached by class

NOTE: Limits should only be hit intentionally, and watch out for excessive (about 25% above HWM) MXT as cause of increased SRM address space's CPU needs!





CICS Dispatcher Domain –2

Processor timings by modes of TCB in CICS V4.1:

QR = Quasi-reentrant (system & **applications**)

CO = Concurrent (VSAM) mode TCB if SUBTSKS is 1

FO = File Owning (VSAM)

RO = Resource Owning

D2 = Used to stop DB2 protected threads

SZ = Used by FEPI interface

RP = Used to make ONC/RPC calls

EP = Runs event processing (new in v4.1)

J8 = Run JVM in CICS key

J9 = Run JVM in user key

JM = Shared class cache management





CICS Dispatcher Domain – 3

Processor timings by modes of TCB in CICS V4.1:

L8 = OPENAPI option and EXECKEY=CICS programs

L9 = OPENAPI option and EXECKEY=USER programs

SO = Used for calls to TCP/IP sockets interface

SL = Used to wait for activity on a set of listening sockets

S8 = Secure Sockets Layer (SSL) or LDAP request

SP = Used for socket pthread owning task

T8 = Used by tasks to perform system processing in JVM server (new in v4.1)

TP = Owns and manages the LE enclave, JVM, THRD TCB pool, and T8 TCB of JVM server (new in v4.1)

X8 = Used by tasks which call C or C++ program compiled with XPLINK option and defined with EXECKEY=CICS

X9 = Used by tasks which call C or C++ program compiled with XPLINK option and defined with EXECKEY=USER





CICS Dispatcher Domain -4

- Number of MVS waits /TCB
- Accum. time in MVS wait /TCB
- Accum. Time dispatched /TCB
- Accum. CPU time /TCB
- **Track & Note:**
 - Total CPU & consumption rate of region
 - Wait-for-dispatch (incl. measurement distortions) = 3 – 4 (w/o capture ratio)





Dispatcher Statistics – Summary

DISPATCHER STATISTICS

Dispatcher Start Date and Time.	: 11/24/2002 09:22:44.7563
Address Space CPU Time.	: 02:11:34.1901
Address Space SRB Time.	: 00:02:24.3700
Peak number of dispatcher tasks	: 149
Peak ICV time (msec).	: 1000
Peak ICVR time (msec)	: 150000
Peak ICVTSD time (msec)	: 250
Peak PRTYAGE time (msec).	: 0
Peak MRO (QR) Batching (MROBTCH) value.	: 1
Number of Excess TCB Scans.	: 1030792M ☹
Excess TCB Scans - No TCB Detached.	: 901943M ☹
Number of Excess TCBs Detached.	: 222681M ☹
Average Excess TCBs Detached per Scan	: 0

.....

Think *Faster* with
Gelb Information




© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Dispatcher Statistics – Summary

DISPATCHER STATISTICS

Dispatcher Start Date and Time.	: 08/23/2009 06:03:32.6499
Address Space CPU Time.	: 00:05:27.182061
Address Space SRB Time.	: 00:00:06.130045
Peak number of dispatcher tasks	: 69
Peak ICV time (msec).	: 1000
Peak ICVR time (msec)	: 2500
Peak ICVTSD time (msec)	: 500
Peak PRTYAGE time (msec).	: 0
Peak MRO (QR) Batching (MROBTCH) value.	: 1
Number of Excess TCB Scans.	: 239
Excess TCB Scans - No TCB Detached.	: 231
Number of Excess TCBs Detached.	: 12
Average Excess TCBs Detached per Scan	: 0
Number of CICS TCB MODEs.	: 21 
Number of CICS TCB POOLs.	: 5

Note: Three new TCB modes in V4.1: EP, T8, TP

Report Source: Steve Ware, from UFL Test Region

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Dispatcher Statistics – Time by TCB Mode

DISPATCHER STATISTICS (Note: Columns 2 - 5 deleted to improve legibility)

TCB Mode	MVS Waits	Total Time in MVS wait	Total Time Dispatched	Total CPU Time / TCB
QR	13051397	000-18:18:33.24	000-01:49:46.74	000-01:12:02.27
RO	48658	000-20:05:12.28	000-00:02:46.27	000-00:01:00.80
CO	0	000-00:00:00.00	000-00:00:00.00	000-00:00:00.00
SZ	0	000-00:00:00.00	000-00:00:00.00	000-00:00:00.00
RP	0	000-00:00:00.00	000-00:00:00.00	000-00:00:00.00
FO	800	000-19:00:52.61	000-00:00:44.05	000-00:00:06.50
SL	1	000-00:00:00.00	000-00:00:00.00	000-00:00:00.00
SO	2	000-00:00:00.00	000-00:00:00.00	000-00:00:00.00
S8	0	000-00:00:00.00	000-00:00:00.00	000-00:00:00.00
D2	2419	000-20:18:01.28	000-00:00:03.26	000-00:00:00.43
L8	16952578	007-03:07:31.31	000-05:36:18.48	000-01:13:35.37
H8	0	000-00:00:00.00	000-00:00:00.00	000-00:00:00.00
J8	0	000-00:00:00.00	000-00:00:00.00	000-00:00:00.00

Recommendation: If QR TCB “Total Time Dispatched” is more than 1.25 times “Total CPU Time/TCB,” determine response time degradation and seek increased importance in WLM Service Policy if degradation is significant.

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



I/O Performance Analysis

- Read I/O Performance
- Write I/O Performance
- RMF Device Activity Reports
- CICS I/O Activity Statistics

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



READ I/O Performance

Performance factors:

- IOS queuing
- Channel utilization
- Amount of cache
- Device utilization
- Intra-file contention
- Inter-file contention
- Path utilization
- I/O pend request handling by CPU

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



WRITE I/O Performance

Performance factors:

- IOS queuing
- Channel utilization
- Amount of NVS cache
- Contention with other writers
- Disk device utilization
- Intra-file contention
- Inter-file contention
- I/O path utilization
- I/O pend request handling by CPU.





I/O Device Activity (RMF PP Report)

DIRECT ACCESS DEVICE ACTIVITY

z/OS VIR8

SYSTEM ID SYS1
RPT VERSION VIR8 RMF

DATE 11/28/2006
TIME 16.30.00

INTERVAL 14.59.946
CYCLE 1.000 SECONDS

TOTAL SAMPLES = 900 IODF = A3 CR-DATE: 07/21/2006 CR-TIME: 07.42.20 ACT: POR

STORAGE GROUP	DEV NUM	DEVICE TYPE	VOLUME SERIAL	PAV	LCU	DEVICE ACTIVITY RATE	AVG RESP TIME	AVG IOSQ	AVG CMR DLY	AVG DB DLY	AVG PEND TIME	AVG DISC TIME	AVG CONN TIME	% DEV CONN	% DEV UTIL	% DEV RESV	AVG NUMBER ALLOC	% ANY ALLOC	% MT PEND
	0401	3380K	SYSLIB		0032	1.246	4.6	0.0	0.0	2.2	2.5	0.1	2.0	0.25	0.26	0.0	89.6	100.0	0.0
	0402	3380K	SYSUSR		0032	0.250	1.4	0.0	0.0	0.1	0.3	0.0	1.0	0.03	0.03	0.1	14.0	100.0	0.0
	040F	3380K	SCL338		0032	0.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00	0.00	0.0	0.0	100.0	0.0
			LCU		0032	1.496	4.1	0.0	0.0	1.0	2.1	0.1	1.8	0.07	0.07	0.0	104	100.0	0.0
	044F	3380K	MVSPG1		0033	0.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00	0.00	0.0	0.0	100.0	0.0
	0460	3380K	RMFLIB		0033	0.036	6.1	0.0	0.0	0.3	1.5	0.0	4.6	0.02	0.02	0.0	0.0	100.0	0.0
	047F	3380K	MVSPLX		0033	0.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00	0.00	0.0	0.0	100.0	0.0
			LCU		0033	0.036	6.1	0.0	0.0	0.3	1.5	0.0	4.6	0.00	0.00	0.0	4.0	100.0	0.0
	0500	33903	MVSLIB		0034	0.082	22.6	0.0	0.0	13.0	16.2	0.3	6.1	0.05	0.05	0.0	20.4	100.0	0.0
	0501	33903	MVSSCF		0034	0.012	1.6	0.0	0.0	0.0	0.5	0.0	1.0	0.00	0.00	0.0	4.6	100.0	0.0
	0502	33903	MVSCI2		0034	0.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00	0.00	0.0	0.0	100.0	0.0
OMVSSYS	0503	33903	MVSOP2		0034	0.008	19.2	0.0	0.0	0.0	0.8	0.0	18.4	0.01	0.01	0.0	0.0	100.0	0.0
	0705	33909	15CY09		0035	0.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00	0.00	0.0	0.0	100.0	0.0
	0707	33909	16RJ02		0035	0.036	55.2	0.0	0.0	36.7	44.6	0.0	10.6	0.04	0.04	0.0	0.0	100.0	0.0
	0708	33909	15CYX9		0035	0.000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00	0.00	0.0	0.0	100.0	0.0

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



RMF Monitor III- Device Delays

RMF V1R8 Device Delays

Line 1 of 57
Scroll ==> HALF

Command ==>

Samples: 100 System: MVS1 Date: 10/31/06 Time: 10.03.20 Range: 100 Sec

Jobname	Service C Class	DLY %	USG %	CON %	Main Delay Volume(s)							
					% VOLSER	% VOLSER	% VOLSER	% VOLSER	% VOLSER	% VOLSER	% VOLSER	% VOLSER
MARYPATM	B NRPRIME	70	51	54	70 TSOL11	1 DUMP00						
MICHAELL	B NRPRIME	39	15	14	39 BPXLK1							
MCPDUMP	S SYSSTC	36	18	20	36 D24PK2							
CHARLESR	B NRPRIME	33	13	13	28 BPXLK1	3 HSML02	2 BPXSSK					
DFHSM	S SYSSTC	30	83	35	10 HSML17	5 SMS026	4 HSMOCD	4 HSMBCD				
SHUMA3	T TSOPRIME	18	52	53	13 D83ID0	5 HSML02						
DAVEP	T TSOPRIME	16	9	10	4 HSM009	3 HSM005	2 HSML06	1 SMS013				
CATALOG	S SYSTEM	9	15	21	2 CLR007	1 HSM036	1 HSM018	1 HSM011				
DB2MDBM1	S SYSSTC	9	7	5	7 DB2MS2	1 DB2MD0	1 DB2MS0					
GINNI	T TSOPRIME	8	10	9	3 HSML17	2 CLR010	1 HSM032	1 NATPK1				
TREVORJ	T TSOPRIME	6	10	11	2 HSM022	1 HSM001	1 RESPK1	1 HSM024				
RHANSON	T TSOPRIME	6	9	8	4 HSML17	1 RESPK1	1 NATPK1					
KOCH	T TSOPRIME	6	3	3	2 HSML17	1 CLR010	1 HSM018	1 HSM043				

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



M3- File I/O Tuning – VSAM RLS

RMF VIR8 VSAM RLS Activity - SYSPLEX Line 1 of 20
Command ==> Scroll == => HALF

Samples: 120 Systems: 2 Date: 10/31/06 Time: 13.25.00 Range: 120 Sec

< 2GB / > 2GB
LRU Status : Good / Accel
Contention % : 0.0 / 0.0
False Cont % : 0.0 / 0.0

VSAM RLS activity by data set.
Also available by Storage Class.

Sphere/DS	Access	Resp Time	----- Read Rate	BMF%	CF%	DASD%	----- Valid%	BMF False	----- Inv%	Write Rate
BMAI.VSAMIN.MEGA										
BMAI.VSAMIN.MEGA.AIX.DATA										
Below 2GB	DIR	0.003	0.01	0.0	0.0	100	0.0	0.00		0.00
	SEQ	0.000	0.00	0.0	0.0	0.0	0.0	0.00		0.00
Above 2GB	DIR	0.003	0.01	0.0	0.0	100	0.0	0.00		0.00
	SEQ	0.000	0.00	0.0	0.0	0.0	0.0	0.00		0.00
BMAI.VSAMIN.MEGA.AIX.INDEX										
Below 2GB	DIR	0.003	0.03	50.0	0.0	50.0	100	0.00		0.00
	SEQ	0.000	0.00	0.0	0.0	0.0	0.0	0.00		0.00
Above 2GB	DIR	0.003	0.03	50.0	0.0	50.0	100	0.00		0.00
	SEQ	0.000	0.00	0.0	0.0	0.0	0.0	0.00		0.00
BMAI.VSAMIN.MEGA.DATA										
Below 2GB	DIR	0.000	7.45	83.2	0.0	16.8	100	0.00		0.00
	SEQ	0.000	0.00	0.0	0.0	0.0	0.0	0.00		0.00

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



CICS File Control Statistics

- FC Calls total by the 7 types: Get, Get Upd, Browse, Update, Add, Delete, Brws Upd
- VSAM Data component physical I/Os
- VSAM Index component physical I/Os


Recommendation: Tuning Objective is to Maximize ratio of:

Σ FC Calls / (Data + Index I/Os)





CICS VSAM File Control Statistics



File Name	Get Requests	Get Upd Requests	Browse Requests	Update Requests	Add Requests	Delete Requests	Brws Upd Requests	VSAM Data	EXCP Index	Requests	RLS req Timeouts
AAAB2SP	34238	0	0	0	0	0	0	22	1	0	0
BBBACTV	0	27	0	27	376636	0	0	382501	0	0	0
CCCFNDD	65928	0	0	0	0	0	0	15089	6228	0	0
DDDIAFD	4767	0	25159	0	0	0	0	12609	148	0	0
EEEINTX	27088	0	8124	0	0	0	0	3	2	0	☺
FFFPNDD	17969	5310	0	5310	166	0	0	9905	799	0	0
GGGSCRX	488	0	0	0	0	0	0	18	59	0	0
HHHSEGH	33043	43	1712	43	43	0	0	1597	841	0	☺
IIISEG1	48931	6925	531	2810	6739	4115	0	15537	2862	0	0
JJJSEG2	23634	745	0	205	745	540	0	1291	1	0	0
KKKTBLs	537	0	75997	0	0	0	0	525	26	0	☺
LLLTEST	0	0	0	0	41741	0	0	43761	0	0	0
MMMULHD	54891	43	0	43	0	0	0	806	453	0	☺
NNNUNLD	32679	1640	0	1586	53	0	0	7319	2670	0	0
OOOPFIL	37752	0	0	0	0	0	0	21	1	0	☺
TOTALS	427489	18626	155690	13864	459660	4655	0	536868	15546	0	0

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



CICS LSR Pools Statistics

LSRPOOLS

Total number of pools built : 17

Peak requests that waited for string : 2

Total requests that waited for string : 125 ☹️ 🦠

Peak concurrently active strings : 6

Shared Buffers

<u>Pool Number</u>	<u>Look- asides</u>	<u>Reads</u>	<u>User writes</u>	<u>Non-user writes</u>
1	644389	48039	4596	0
2	53249	824	0	0 ☺️
3	234800	2568	139	0 ☺️
4	83125	5164	5620	0
5	187335	21327	1658	0
6	23980	10	24460	0
7	397988	7033	12882	0 ☺️
8	86917	1443	1507	0
TOTALS	1711783	86408	50862	0

Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Temporary Storage

```
Put/Putq main storage requests      :      78701 <
Get/Getq main storage requests      :      70899 <
Peak storage for temp. storage (main) :    135916 <
Put/Putq auxiliary storage requests :      78756 <
Get/Getq auxiliary storage requests :    135961 <
Peak temporary storage names in use  :         66
Number of entries in longest queue   :         58
Times queues created                 :    131425
Control interval size                :         4096
Available bytes per control interval :         4032
Segments per control interval        :         63
Bytes per segment                    :         64
Writes more than control interval    :          3
Longest auxiliary temp storage record :     32080
Number of control intervals available :     3599
Peak control intervals in use        :         13
Times aux. storage exhausted         :          0 <
Number of temp storage compressions  :     1507 <
Temporary storage buffers            :          6 <
Buffer waits                         :          0 <
Peak users waiting on buffer         :          0 <
Buffer writes                        :         22 <
Forced writes for recovery           :          0 <
Buffer reads                         :         25 <
Format writes                        :          0 <
Temporary storage strings            :          6 <
Peak number of strings in use        :          1 <
Times string wait occurred           :          0 <
Peak number of users waiting on string :          0 <
I/O errors on TS dataset             :          0 <
Shared pools defined                 :          0
Shared pools currently connected     :          0
Shared read requests                 :          0
Shared write requests                :          0
```

Think *Faster* with
Gelb Information




© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333



Transient Data

```
TRANSIENT DATA
Control interval size           :           4096
Peak control intervals used     :             2
Times NOSPACE occurred         :             0 <
Writes to intrapartition dataset :             0
Reads from intrapartition dataset :             0
Formatting writes               :             0
I/O errors                      :             0 <
Intrapartition buffers         :             3
Peak intra. buffers containing valid data :             1
Intrapartition accesses       :             5
Peak concurrent intrapartition accesses :             1
Intrapartition buffer waits    :             0 < □
Peak intrapartition buffer waits :             0 < □
Times string accessed          :             0
Peak concurrent string accesses :             0
Intrapartition string waits    :             0 < □
Peak string waits              :             0 < □
```





Four Other Areas to Analyze


- Virtual storage activity and use to prevent any SOS
 - Storage compression is precursor to SOS
- Real storage activity – page-ins can cause severe pain
- Program load activity – should be minimal once loaded
 - Program compressions are a sign of insufficient virtual storage
- DB2 threads allocations and activity





Be @Next SHARE / Any Questions?

Join us at the next SHARE in 2014.



Think *Faster* with
Gelb Information



© 2013 Gelb Information Systems Corp.

Any questions? Email to: ivan@gelbis.com; Call: 732-303-1333