

IPv6 BasicsShare Anaheim Session 14497



Laura Knapp
WW Business Consultant
Laurak@aesclever.com

ipv6hawaii@outlook.com



What is IPv6

Updated version of the Internet Protocol (IPv4)

Defined in RFC 1752

New features

Larger address space

Encapsulation

Class of service for audio, video, etc.

Multicast support

Authentication

Encryption

Automatic configuration/reconfiguration


Support for non-IP protocols

Coexist with IPv4





Why Do We Need More Address Spaces?




February 2011 – NRO (Number Resource Organization of the IANA) allocated the last IPv4 addresses to RIR

Microsoft paid \$7.5M for Nortels 666,624 IPv4 addresses

Trading sites like Tradipv4.com have emerged



IPv4 address allocation by /8









IPv6 Technology Scope

| | | _ | | 9 | _ |
|--|--------------|----|---|-----|---|
| | | | r | /// | e |
| | \mathbf{U} | G. | ľ | | |

Addressing Range

Autoconfiguration

Security

Mobility

Quality-of-Service

IP Multicast

IPv4 Solution

32-bit, Network Address Translation

DHCP

IPSec

Mobile IP

Differentiated Service, Integrated Service

IGMP/PIM/Multicast BGP

IPv6 Solution

128-bit, Multiple Scopes

Serverless, Reconfiguration, DHCP

IPSec Mandated, works End-to-End


Mobile IP with Direct Routing

Differentiated Service, Integrated Service

MLD/PIM/Multicast BGP, Scope Identifier



IPv6 Address Size



Asia feeling address squeeze fastest due to receiving addresses last


Mobil digital telephony pressuring existing IPv4 network

ICANN continues to handle overall addressing issues


Shortcuts like dropping Leading zeros or C ontiguous zeros permitted



IPv6 Header IPv4 Header



IPv6 Header




IPv4 header is 20 bytes: IPv6 header is 40 bytes
Address increased from 32 to 128 bits
Fragmentation fields moved out of base header
Header checksum
Time to Live replaced with 'Hop Limit'
Protocol replaced with 'Next Header'
TOS replaced with 'Flow Label'
Alignment changed from 32 to 64 bits



IPv6 Flow Label

IPv6 Header



Identifies datagrams that require special quality of service

May be used to tie particular traffic to pre-allocated network resources

Zero value indicates no flow label

Other protocols like RSVP may provide information for the Flow Label


TC class identifies delivery of priority packets


Values 0-7 : TCP flow controlled packets

Values 8-15: real time packets




IPv6 Extension Headers









Hop by hop options = 0
Information for all devices in the path

Destination options = 60
Destination information for all devices

Routing = 43
Specify route for a datagram

Fragment = 44
Breaks datagram if MTU exceeded

Encapsulating Security Payload = 50 Encryption type and parameters


Authentication = 51
Hash type and parameters

Destination options = 60
Information only for destination host

Protocols TCP = 6, UDP = 17, RSVP = 46, ICMP = 58




IPv6 Fragmentation Header



In IPv4 Routers handled fragmenting frames

If needed, IPv6 hosts fragment frames:
Increased guaranteed minimum MTU of 1280
Pat MTU discovery to find maximum fragment size for a path





IPv6 Security



Authentication Header (AH)

Packet authentication and integrity without confidentiality Algorithm independent (MD5) (SHA1)

Data Privacy Header (ESP)

Message including next headers encrypted

Mandatory support of DES-CBC

May also include AH with no separate header



IPv6 Address Types


unicast:

for one-to-one communication



multicast:

for one-to-many communication



anycast:

for one-to-nearest communication






Link Local Address



- FE80 prefix
- Similar to IPv4 APIPA (169.254.0.0/16)
- Only for on-link communication, not routable
- Used for
 - Auto configured addresses
 - Neighbor discovery process



Multicast Address



Flags

0: well known address, 1: transient address

Scope

1: Node Local (FF01::1), 2: Link Local (FF02::1)

All routers group: FF02::2)

Group ID

1: All nodes, 2: All routers, 101: all NTP servers

- Multicast replaces Broadcast
- All IPv6 nodes must support multicast
- You must enable IGMP snooping



Global Unicast Address

3 bits 45 bits 16 bits 64 bits

001 routing prefix subnet id interface id

| Address Type | Binary Prefix | Prefix |
|------------------|-------------------|----------|
| Unspecified | 0000 | ::/128 |
| Loopback | 000001 | ::1/128 |
| ULA | 1111 110 | FC00::/7 |
| Assigned to RIRs | 001 | 2003:/3 |
| Global Unicast | Everything else!! | |


Korea: 2001:0200 - 099F

ATT: 2001:0408/32

Verizon: 2001:0506:0000/48



Unique Local Address (ULA)



- L=1
- FC00::/7 prefix
- Local or site local communications
- Most likely will be unique and not expected to be routable
- Well known, somewhat like the RFC1918



Windows and IPv6

IPv6 is preferred

Nameserver query

Try to reach IPv6

Try to reach IPv4

Timeout

```
Wireless LAN adapter Wireless Network Connection 2:
  Media State . . . . . . . . . . . . . . . . Media disconnected
  Connection-specific DNS Suffix . :
Wireless LAN adapter Wireless Network Connection:
  Media State . . . . . . . . . . . . . . . . Media disconnected
  Connection-specific DNS Suffix . :
Ethernet adapter Local Area Connection:
  Connection-specific DNS Suffix . : hawaii.rr.com
  Link-local IPu6 Address . . . . . : fe80::6947:83b1:88e2:73d4%13
  IPv4 Address. . . . . . . . . . . . . . . 192.168.1.146
  Default Gateway . . . . . . . . . . . 192.168.1.1
Ethernet adapter Bluetooth Network Connection:
  Media State . . . . . . . . . . . . . . . . . Media disconnected
  Connection-specific DNS Suffix . :
Tunnel adapter Teredo Tunneling Pseudo-Interface:
  Connection-specific DNS Suffix . :
  IPu6 Address. . . . . . . . . . . . . . . . 2001:0:4137:9e76:10f7:1e4b:9d69:43f8
  Link-local IPv6 Address . . . . . : fe80::10f7:1e4b:9d69:43f8%15
  Default Gateway . . . . . . . . : ::
Tunnel adapter isatap.hawaii.rr.com:
  Media State . . . . . . . . . . . . . . Media disconnected
  Connection-specific DNS Suffix . : hawaii.rr.com
```



Interface ID from MAC






IEEE 48-Bit MAC Address



Expand to EUI-64




Invert the Global Bit

0219: 71FF: FE64: 3F00

Interface ID



Boundaries





IPv6: Autoconfiguration

Combination

ARP: ICMP router discovery: ICMP redirect

Neighbor discovery

Multicast and unicast datagrams

Establishes MAC address on same network

ICMPv6 router solicitation

ICMPv6 router advertisement

ICMPv6 neighbor solicitation

ICMPv6 redirect

ICMPv6 includes IGMP protocol for Multicast IP

Reduces impact of finding hosts

Stateless: router configures a host with IPv6 address


Stateful: DHCP for IPv6

Link Local Address: IPv6 connectivity on isolated LANs





IPv6 Auto-configuration



Host 1 comes on line and generates a link local address

Host 1 sends out a query called neighbor discovery to the same address to verify uniqueness. If there is a positive response a random number generator is used to generate a new address

Host 1 multicasts a router solicitation message to all routers

Routers respond with a router advertisement that contains an aggregatable global address (AGA) prefix and other information

Host 1 automatically configures its global address by appending its interface ID to the AGA

Host 1 can now communicate



Changes Needed to Implement IPv6

Hosts

Implement IPv6 code in operating system

TCP/UDP aware of IPv6

Sockets/Winsock library updates for IPv6

Domain Name Server updates for IPv6

Domain Name Server (DNS)

Many products already support 128 bit addresses

Uses 'AAAA' records for IPv6

IP6.INT (in_addr_arpa in IPv4)

Routers

IPv6 forwarding protocols

Routing protocols updated to support IPv6

Management needs to support ICMPv6

Implement transition mechanisms

IPv6 Protocol Status

RIPv6 - Same as RIPv2

OSPFv6 - Updated for IPv6

EIGRP - Extensions implemented

IDRP - Recommended for exterior protocol over BGP4

BGP4+ - Preferred implementation in IPv6 today





Considerations

customer

- Network impact is minimal, the user is no-perceived.
- IPv6 users visit IPv4 service.
- Enhance the user experience of IPv6

cost

- Weighed between the cost of reconstruct and upgrade, choose the time to introduce
- IPv6 mobile services, dual stack terminal cost, singlestack terminal need large volume of NAT-PT.

IPv6 Deployment

network

- Reduce impact to the network, consider build a new private network, using an independent IPv6 Gateway to access IPv6 users
- Consider the end-to-end deployment of IPv6.

service

- Start from closed business, interoperability is undemanding, easy to deploy.
- IPv4/IPv6 will be long-term coexistence.
- Integrated service intercommunication



Applications



NTT Technical Review

- NTT 'Earthquake Alert Service
 - On detecting P-wave an S-wave alert is delivered
 - IPv6 Multicast is adopted
 - Low delay delivery is achieved
 - IPv4 is not suitable for a push-type service due to NAT
- Sensor Arrays
 - 6LoWPAN (RFC 4919and 4944) based networks
 - Routing over low poer and Lossy Networks
 - Sensors on aging infrastructure
 - Fire sensors
- Chinese Academy of Sciences
 - Integrated wireless, control and precision agriculture technologies linked
 - Accurate watering of farmland
 - Water/soil pollution monitoring



IPv6 Deployment

| China Telecom 中国电话 CHINA TELECOM | 2009 deploy Experimental IPv6 network, in 2010 commercialized. T he Telecommunications Research Institute draft guidance of large-scale IPv6 introduction, Hunan Telecom starts IPv6 test point. In 2010 Shanghai World Expo and Guangzhou Asian Games displayed IPv6. |
|--|--|
| China mohila 中国移动通信 中国移动通信 中国科 MOBIE 2. 至2004年 和亚安古代 明年 Anner of the Reign (2001) person times | 3G mobile broadband deploy IPV6, to resolve the limitation of private network address space. The original IPv4 reserve is very limited, the mobile broadband has more requirements. 2010, China mobile deployed 3G IPv6 commercial services. |
| China Unicom China unicom中国联通 | 2010 commercial-scale test users reached 20,000, China Unicom built a new type IPv6 access network |
| France Telecom | 2009 Q2-Q3 FT deployed Enterprise IPV6, in 2010 deployed the family IPv6 Livebox, the Core network maintains IPv4 temporarily. Poland subnet has strong interest, actively discusses the deployment of IPv6 solution, requests the current network equipment support dual-stack. |
| Japan ONTT Group | IPv6 large-scale commercial from 2005, package the new concept of next-generation network, provide high-speed network services based on IPv6, leveraging next-generation network evolution, and promote various IPv6 new technologies and new services. |
| America | The U.S. government required government and Defense departments migrate telecommunication network into IPv6 platform before the summer of 2008. It led that the United States new applied IPv6 addresses reached 14,729 pieces, the world's ranking jumped from No. 11 to No. 1. |



NTT and IPv6

NTT Global IPv6 Service Availability





1.Latency Statistics(ms)

| Month | Intra- Japan (25ms) | Intra- Asia (95ms) | Intra- US (60ms) | Intra- Europe (35ms) | Trans- Atlantic (90ms) | US- Japan (130ms) | Japan- Europe (300ms) |
|----------|---------------------------|--------------------------|------------------------|----------------------------|------------------------------|-------------------------|-----------------------------|
| Oct 2012 | 10.39 | 51.17 | 44.30 | 23.26 | 72.31 | 105.49 | 262.25 |
| Nov 2012 | 9.68 | 52.53 | 44.17 | 23.36 | 72.01 | 103.24 | 262.07 |
| Dec 2012 | 10.18 | 57.55 | 43.88 | 23.39 | 71.99 | 93.63 | 224.09 |


2.Packet Loss Statistics(%)

| Month | Intra- Japan | Intra- US | Trans- Atlantic | Japan- US | Intra- Asia | Intra- Europe | Japan- Europe |
|----------|-----------------|--------------|--------------------|--------------|----------------|------------------|------------------|
| Oct 2012 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Nov 2012 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Dec 2012 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |




IPv6 and the US Government





- Detailed IPv6 & DNSSEC Service Interface Statistics for 2013.07.08 -

| Domain | Domain Organization | | Mail | Web | DNSSEC |
|---------------------------|--|---------------|---------------|---------------|--------------|
| gov.404. | Securities and Exchange Commission | [8] 3/2/2 [0] | [0] 0/0/0 [-] | [3] 0/0/0 [I] | s/v/c |
| gov.9-11commission. | National Archives and Records Administration | [2] 2/2/2 [0] | [0] 0/0/0 [-] | [1] 0/0/0 [I] | s/v/c |
| gov.911. | Department of Transportation | [3] 3/0/3 [0] | [0] 0/0/0 [-] | [1] 0/0/0 [I] | s/v/c |
| gov.911commission. | National Archives and Records Administration | [2] 2/2/2 [0] | [0] 0/0/0 [-] | [1] 0/0/0 [I] | s/v/c |
| gov.aapi. | Department of Education | [4] 4/0/4 [0] | [0] 0/0/0 [-] | [1] 1/0/1 [I] | S/V/C |
| gov.abandonedmines. | Department of the Interior | [6] 4/4/4 [0] | [1] 0/0/0 [0] | [1] 0/0/0 [I] | S/V/C |
| gov.abilityone. | Comm for People Who Are Blind/Severly Disabled | [2] 2/2/2 [0] | [1] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| gov.abmc. | American Battle Monuments Commission | [2] 0/0/0 [0] | [2] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| gov.access-board-members. | U. S. Access Board | [4] 4/4/4 [0] | [0] 0/0/0 [-] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| gov.access-board. | U. S. Access Board | [2] 0/0/0 [0] | [2] 0/0/0 [0] | [1] 1/0/0 [I] | <u>U/-/-</u> |
| gov.acf. | Department of Health And Human Services | [4] 4/4/4 [0] | [0] 0/0/0 [-] | [1] 0/0/0 [0] | s/v/c |
| gov.achp. | Advisory Council on Historic Preservation | [4] 2/0/2 [0] | [2] 0/0/0 [I] | [1] 0/0/0 [I] | s/v/c |
| gov.acquisition. | General Services Administration | [6] 2/0/2 [0] | [0] 0/0/0 [-] | [1] 0/0/0 [I] | s/v/c |
| gov.acus. | Administrative Conference of the United States | [6] 2/0/2 [0] | [2] 0/0/0 [0] | [1] 0/0/0 [I] | s/v/c |
| gov.acwi. | Department of the Interior | [6] 6/0/6 [0] | [2] 0/0/0 [0] | [6] 6/4/4 [0] | s/v/c |



http://usgv6-deploymon.antd.nist.gov/cgi-bin/generate-gov



IPv6 and Industry

Industry Unique Configured Service Interfaces for 2013.07.08 - 1070 Domains Measured -




http://usgv6-deploymon.antd.nist.gov/cgi-bin/generate-gov



IPv6 and University

University Unique Configured Service Interfaces for 2013.07.07 - 346 Domains Measured -




- Detailed IPv6 & DNSSEC Service Interface Statistics for 2013.07.07 -

| Domain | Organization | DNS | Mail | Web | DNSSEC |
|---------------|-------------------------------------|------------------|---------------|---------------|--------------|
| edu.uakron. | University of Akron | [2] 0/0/0 [I] | [2] 0/0/0 [0] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.aamu. | Alabama A&M University | [4] 0/0/0 [M] | [1] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.alasu. | Alabama State University | [5] 0/0/0 [0] | [5] 0/0/0 [M] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.uab. | University of Alabama at Birmingham | [5] 2/2/2 [M] | [2] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.ua. | University of Alabama Tuscaloosa | [3] 0/0/0 [M] | [2] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.albany. | University at Albany | [5] 2/2/2 [M] | [1] 0/0/0 [0] | [1] 1/1/1 [I] | <u>U/-/-</u> |
| edu.alcorn. | Alcorn State University | [2] 0/0/0 [I] | [1] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.american. | American University | [4] 0/0/0 [I] | [3] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.appstate. | Appalachian State University | [2] 0/0/0 [I] | [1] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.arizona. | University of Arizona | [5] 0/0/0 [M] | [1] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.asu. | Arizona State University | [4] 0/0/0 [I] | [4] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.astate. | Arkansas State University | [4] 1/0/0 [M] | [1] 0/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| edu.uark. | University of Arkansas Fayetteville | [2] 0/0/0 [I] | [3] 2/0/0 [I] | [1] 0/0/0 [I] | <u>U/-/-</u> |
| | and the second control of | 5.43 O /4 /4 573 | 553 4/4/4 503 | rea 0/0/0 rea | 0.07.10 |

http://usgv6-deploymon.antd.nist.gov/cgi-bin/generate-gov



6lab.cisco.com





IPv6 Statistics 6lab.cisco.com/stat



Romania

IPv6 overall deployment: 78.05%

Detail: Prefixes: 55.7% | Transit AS: 47.81% | Content: 46.02% | Users: 8.74%

United States of America

IPv6 overall deployment: 44.79%

Detail: Prefixes: 41.88% | Transit AS: 58.66% | Content: 47.08% | Users: 2.46%



IPv6 overall deployment: 62.33%

Detail: Prefixes: 46.24% | Transit AS: 68.31% | Content: 48.47% | Users: 5.11%

India

IPv6 overall deployment: 36.61%

Detail: Prefixes: 13.96% | Transit AS: 70.43% | Content: 51.94% | Users: 0.24%

Brazil

IPv6 overall deployment: 28.59%

Detail: Prefixes: 18.26% | Transit AS: 34.89% | Content: 52.79% | Users: 0.04%



Google IPv6 Statistics






Google Statistics on IPv6 continuous usage http://www.google.com/ipv6/statistics.html#



IPv6 Networks Advertised





IPv6 Transition Methods

Tunneling

IPv6 only systems communicate across an IPv4 network

Header translation


IPv6 system communicates with an IPv4 system (header conversion, transport relay, application proxy)

Dual Stack






Enterprise Content



Availability of enterprise content over IPv6




IPv6 Edge Deployment





IPv6 Enterprise Deployment





Why IPv6 in Korea?

Prepare IPv4 Address Depletion

- Usage ratio of assigned IP addresses : 96.2% (Mar. 2006)
 - More IP addresses to be needed for the future IT839 Strategy

Promoting New

Services

IPv6 based Home Network Service

- IPv6 Service over 2.3 GHz based WiBro
- IPv6 based VoIP Service
- IPv6 based Telematics Service, and many others

IT839 New Growth Engine

- A master plan for the IT industry
- Effort to gain more growth momentum from the IT sectors



6to4 Tunneling

IPv6 traffic tunneled to go through an IPv4 network www.sixxs.net – Worldwide tunnel broker

Address - 2002:wwxx:yyzz::/48
wwxx:yyzz is both the NLA and the colonhexadecimal representation of an IPv4 address
assigned to the site or host


2002:wwxx:yyzz:[Subnet]:{Interface ID}

6to4 host - an IPv6 host that is configured with at least one 6to4 address

6to4 router - an IPv4/IPv6 router that forwards 6to4 traffic between 6to4 hosts within a site or 6to4 relay routers on the IPv4 Internet

6to4 relay router - an IPv4/IPv6 router that forwards 6to4 addressed traffic between 6to4 routers on the IPv4 Internet and hosts on IPv6 networks Anycast


2002:C058:6301::





Teredo

- 6to4 tunnels requires the tunnel end point public IPv4 address.....so for many that many NAT device...Many NAT devices cannot the upgraded
- Teredo encapsulates IPv6 in UDP/IPv4 datagrams.
 - Diagnoses UDP over IPv4 (UDPv4) connectivity and discovers the kind of NAT
 - assigns a globally-routable unique IPv6 address to each host using it;
 - encapsulates IPv6 packets inside UDPv4 datagrams for transmission over an IPv4 network (this includes <u>NAT</u> <u>traversal</u>);
 - routes traffic between Teredo hosts and native (or otherwise non-Teredo) IPv6 hosts.





IPv6 Translations

NAT-PT (Network Address Translation and Protocol Translation)\

Translates by mapping each IPv6 address onto one from a pool of IPv4 addresses

Upside: easy to implement and understand

Downside: Limits simultaneous access to multiple services with a network

Breaks end-end networking

Single point of failure

NAPT-PT (Network Address Translation plus Port Translation)

Protocol gateway translates the IPv4/IPv6 network addresses and also maps port across boundaries

Upside: Easy to implement, adds support for more simultaneous sessions

Downside: Breaks end-end networking, single point of failure

SIIT (Stateless IP/ICMP Translation)


IP packets and ICMP messages are translated between IPv4 and IPv6 with temporary assignments of IPv4 addresses creating a one-one mapping

Upside: Does not require state detail to be maintained

Downside: Does not save on IP addresses, single point of failure



IPv6 BGP Weathermap – Prefixes per Country





IPv6 Migration Plans

Define topology and functions on hosts, routers, and service machines

Upgrade DNS, DHCP, ARP servers to handle IPv6 addresses

Introduce dual stack systems that support IPv4 and IPv6

Configure to Internet using IPv6

Rely on tunnels to connect IPv6 islands separated by IPv4 networks

Gradually remove IPv4 from systems

Work closely with ISP for connections to the Internet





IPv6 References

http://www.ietf.org/

http://playground.sun.com/pub/ipng/html/ipng-main.html

http://www.getipv6.info/index.php/IPv6_Presentations_and_Documentshttp://www.6ren.net

http://www.ipv6forum.com

http://arin.net

http://www.internet2.edu

http://www.ipv6.org

http://ipv6.or.kr/english/natpt.overview

http://www.research.microsoft.com/msripv6

http://www.ipv6.org.uk

New Internet Protocol - Prentice Hall - ISBN 0-13-241936-x

IPNG and the TCP/IP Protocols - John Wiley and Sons - ISBN-0-471-13088-5

IPv6 The New Internet Protocol - ISBN-0-13-24-241936

IPNG Internet Protocol Next Generation - ISBN-0-201-63395-7

Internetworking IPv6 with Cisco Routers - ISBN 0-07-022831-1





AES Sessions

| Session | Title | Day | Time | Room |
|---------|---|-------------------------|----------|---------------|
| 12152 | IPv6 Basics | Tuesday February 5 | 1:30 PM | Golden Gate 4 |
| 12777 | Network Problem Diagnosis with Packet Traces | Wednesday February 6 | 9:30 AM | Golden Gate 3 |
| 12778 | Performance Factors in Cloud Computing | Wednesday February 6 | 11:00 AM | Golden Gate 4 |
| 12150 | I'm Running IPv6 How Do I Access? | Wednesday February 6 | 3:00 PM | Golden Gate 4 |
| 12158 | Managing an IPv6 Network | Thursday February 7 | 11:00 AM | Golden Gate 4 |
| 12149 | Kick Start your IPv6 Skills using your home network | Friday February 8 | 8:00 AM | Golden Gate 4 |
| 12153 | IPv6 Deep Dive | Friday February 8 | 9:30 AM | Golden Gate 4 |





ありがとうございました































감사합니다

Tesekkürler



650-617-2400

Obrigado

1011111