



XEDIT, EXECs & PIPES

Bob Bates
Wells Fargo Bank



SHARE is an independent volunteer-run information technology association that provides education, professional networking and industry influence.



Disclaimer



- The information and opinions found herein are for informational sharing purposes only and not necessarily those of Wells Fargo Bank and should not be considered an endorsement.

Agenda

- Who I Am
- XEDIT
- EXECs
- PIPEs

Who is Bob?

- Systems programmer for z/VM and Linux on z Series at Wells Fargo
- AVP, Operating Systems Engineer
- Enterprise Hosting Services
- At WF since 2007
- 8 team members
- Install/support/engineer Linux on z and z/VM builds
- Level 2-3 for all Linux on z servers
- VM System Programmer since 1980 (VM/SP Release 1.0)
- VM user since 1977 (VM/370 Release 4)

New system – Create my userid



- Logon to MAINT630
- DISKMAP USER DIRECT
- XEDIT USER DIRECT

Complete your session evaluations online at www.SHARE.org/Orlando-Eval



Vanilla XEDIT on MAINT630

```
USER      DIRECT  C1  F 80  Trunc=72 Size=4733 Line=0 Col=1 Alt=0

00000 * * * Top of File * * *
00001 *****
00002 *  z/VM 6.3.0  SYSTEM DIRECTORY                               *
00003 *****
00004 *                                                                 *
00005 *  THE ADDRESSES 123 THROUGH 133 ARE VIRTUAL ADDRESSES.      *
00006 *                                                                 *
00007 *  NOTES:                                                       *
00008 *  REMEMBER THESE ARE ONLY VIRTUAL ADDRESSES NOT REAL        *
00009 *  ADDRESSES, SO THERE IS NO NEED TO CHANGE THEM TO MATCH    *
00010 *  YOUR HARDWARE ADDRESSES.                                     *
00011 *                                                                 *
00012 *                                                                 *
00013 *****
00014 *                                                                 *
00015 *  FOR A DESCRIPTION OF DIRECTORY STATEMENTS SEE:              *
00016 *    VM ENTERPRISE SYSTEM ARCHITECTURE                          *
00017 *    PLANNING AND ADMINISTRATION MANUAL.                        *
00018 *                                                                 *
00019 *****
00020 *                                                                 *
00021 *                                                                 *
00022 *                                                                 *
00023 DIRECTORY SSI 123 3390 VHFRES VHERES VH6RES
====> f USER CMS_

AB  :00.1 27/017
```

Copy the entry

```
USER      DIRECT  C1 F 80 Trunc=72 Size=4733 Line=555 Col=1 Alt=0

cc555 USER CMS1      WD5JU8QP  32M  64M G
00556 INCLUDE IBMDFLT
00557 AUTOLOG AUTOLOG1 OP1 MAINT
00558 ACCOUNT ACT4 CMSTST
00559 MACH ESA
00560 IPL 190
00561 *
00562 *****
cc563 *
00564 IDENTITY CMSBATCH WD5JU8QP  32M  32M G
00565 BUILD ON VMHCF USING SUBCONFIG CMSBAT-1
00566 BUILD ON VMHCE USING SUBCONFIG CMSBAT-2
00567 BUILD ON VMHC6 USING SUBCONFIG CMSBAT-3
00568 * BUILD ON @@member4name USING SUBCONFIG CMSBAT-4
00569 ACCOUNT 3 SYSTEM
00570 MACH ESA
00571 OPTION ACCT
00572 IPL 190 PARM AUTOGR
00573 CONSOLE 009 3215
00574 SPOOL 00C 2540 READER *
00575 SPOOL 00D 2540 PUNCH A
00576 SPOOL 00E 1403 A
00577
00578 SUBCONFIG CMSBAT-1
====> bot_

4B  :00.1 27/010
```

USER DIRECT C1 F 80 Trunc=72 Size=4733 Line=4733 Col=1 Alt=0

f4733 MDISK 191 3390 333 20 VHPP01 MR
04734 * * * End of File * * *

====>

AB

:00.1

03/002

USER DIRECT C1 F 80 Trunc=72 Size=4742 Line=4733 Col=1 Alt=1

```
c4733 MDISK 191 3390 333 20 VHPP01 MR
04734 USER MYNEWID MYNEWPWD 32M 64M G
04735 INCLUDE IBMDFLT
04736 AUTOLOG AUTOLOG1 OP1 MAINT
04737 ACCOUNT ACT4 CMSTST
04738 MACH ESA
04739 IPL 190
04740 *
04741 *****
f4742 *
04743 * * * End of File * * *
```

====>



00:00.1

12/002

Edit a 2nd file

```
USER   DIRECT  C1 F 80 Trunc=72 Size=4743 Line=4733 Col=1 Alt=2

04733  MDISK 191 3390 333  20 VHPP01 MR
04734  USER CMS1   WD5JU8QP  32M  64M G
04735  INCLUDE IBMDFLT
04736  AUTOLOG AUTOLOG1 OP1 MAINT
04737  ACCOUNT ACT4 CMSTST
04738  MACH ESA
04739  IPL 190
04740  *
04741  *****
04742  *
04743  MDISK 191 3390 333  20 VHPP01 MR
04744  * * * End of File * * *

====> x user diskmap_
4B | :00.1 | 27/021
```

Did F VHPP01

```
USER      DISKMAP  A1  F 100  Trunc=100  Size=705  Line=508  Col=1  Alt=0

00508 VHPP01  VMANAGER  0191  3390  00001  00005  00005  *
00509      VMANAGER  051D  3390  00006  00010  00005  *
00510      VMANAGER  0193  3390  00011  00025  00015  *
00511      VMANAGER  0195  3390  00026  00040  00015  *
00512      VMANAGER  01FF  3390  00041  00045  00005  *
00513      ZVMN012A  02C4  3390  00046  00046  00001  *
00514      ZVMN012A  02A6  3390  00047  00047  00001  *
00515      ZVMN012A  02A2  3390  00048  00048  00001  *
00516      49      49      1      GAP
00517      ZVMN012A  0210  3390  00050  00064  00015  *
00518      ZVMN012A  0214  3390  00065  00065  00001  *
00519      ZVMN012A  0216  3390  00066  00066  00001  *
00520      ZVMN012A  02C2  3390  00067  00067  00001  *
00521      ZVMN012A  02B2  3390  00068  00097  00030  *
00522      ZVMN012A  02D2  3390  00098  00102  00005  *
00523      ZVMX031A  02C4  3390  00103  00107  00005  *
00524      ZVMX031A  02A6  3390  00108  00112  00005  *
00525      ZVMX031A  02A2  3390  00113  00117  00005  *
00526      ZVMX031A  02D2  3390  00118  00122  00005  *
00527      ZVMX031A  0210  3390  00123  00137  00015  *
00528      ZVMX031A  0212  3390  00138  00139  00002  *
00529      ZVMX031A  0214  3390  00140  00140  00001  *
00530      ZVMX031A  02C2  3390  00141  00142  00002  *
00531      ZVMX031A  0218  3390  00143  00152  00010  *

====> xe_

[4B]  @:00.1  27/009
```

USER DIRECT C1 F 80 Trunc=72 Size=4743 Line=4733 Col=1 Alt=2

```
04733 MDISK 191 3390 333 20 VHPP01 MR
04734 USER CMS1 WD5JU8QP 32M 64M G
04735 INCLUDE IBMDFLT
04736 AUTOLOG AUTOLOG1 OP1 MAINT
04737 ACCOUNT ACT4 CMSTST
04738 MACH ESA
04739 IPL 190
04740 *
04741 *****
04742 *
04743 MDISK 191 3390 49 1 VHPP01 MR
04744 * * * End of File * * *
```

====> file_

4B

@:00.1

27/011

XEDIT

- XEDIT fn ft fm (Width size PROFILE PROFILE|fname *other options*
 - If fm omitted, locates first file in access order, or creates new file on A.
 - Width defines the lrecl on RECFM V overriding default
- XEDIT is a full screen editor
- Flexible, customizable
- XEDIT Macros can be written using EXEC languages (filetype XEDIT)
- XEDIT invokes PROFILE XEDIT, set preferences in there:
 - /* XEDIT PROFILE */
 - ‘SET SCALE OFF’
 - ‘SET NUM ON’
 - ‘SET SHADOW OFF’

Filetypes

- The filetype sets some features such as RECFM, LRECL, VERIFY, TRUNC, SERIAL, TABS and others.
 - LISTING V 121
 - ASSEMBLE F 80 SERIAL ON 10 10
 - EXEC V 130
 - XEDIT V 255
 - Many are F 80

Look in XEDIT Commands and Macros for a table of all defaults

Create: XEDIT PROFILE XEDIT

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=0 Line=0 Col=1 Alt=0
DMSXIN571I Creating new file:

===== * * * Top of File * * *
|...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...8...+...9...+...10...+...11...+...12...+
===== * * * End of File * * *

=====> j /* This is my PROFILE XEDIT */_

XEDIT 1 File

4B 00:00.1 26/039
```

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=1 Line=1 Col=1 Alt=1
```

```
==== * * * Top of File * * *  
==== /* THIS IS MY PROFILE XEDIT */  
|...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...8...+...9...+...10...+...11...+...12...+  
==== * * * End of File * * *
```

```
====> status_
```

XEDIT 1 File

4B

00:00.1

26/013


```
APL OFF          IMAGE ON          SCOPE DISPLAY
ARBCHAR OFF $   IMPCMSCP ON       SERIAL OFF 10 10
AUTOSAVE OFF    LINEND ON #     SHADOW ON
BFSLINE NL      LRECL 255          SPAN OFF BLANK 2
CASE UPPER RESPECT ← MACRO OFF          SPILL OFF
CMDLINE ON      MSGLINE ON 2 2    STAY OFF ←
COLPTR OFF      MSGMODE ON LONG  STREAM ON ←
CURLINE ON M    NAMETYPE CMS     SYNONYM ON
DISPLAY 0 0     NONDISP "          TABLINE OFF -3
ESCAPE OFF /    NULLS OFF          TERMINAL DISPLAY
ETMODE OFF      NUMBER OFF ←    TEXT OFF
FILLER          PACK OFF          TOFEOF ON
FMODE A1        PREFIX ON LEFT ← TRUNC 255
FNAME PROFILE   RANGE :1 :1     VARBLANK OFF
FTYPE XEDIT     RECFM V          WRAP OFF ←
FULLREAD OFF    REMOTE OFF       ZONE 1 255
HEX OFF         SCALE ON M+1 ←
```

```
SCREEN SIZE 27
MASK
TABS 1 4 7 10 13 16 19 22 25 31 37 43 49 55 79 80
VERIFY OFF 1 255
CTLCHAR OFF
COLOR ARROW     DEFAULT NONE HIGH PS0
COLOR CMDLINE  DEFAULT NONE NOHIGH PS0
```

MORE... VMHCF

MB

@:00.1

26/001

Did CASE M I then PF6 to retrieve I command change I to R

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=1 Line=1 Col=1 Alt=1
```

```
==== * * * Top of File * * *
==== /* THIS IS MY PROFILE XEDIT */
     |...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...8...+...9...+...10...+...11...+...12...+
==== * * * End of File * * *
```

```
====> r_/* This is my PROFILE XEDIT */
```

XEDIT 1 File

4B

@:00.1

26/008

Replaced line and going into Input mode

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=1 Line=1 Col=1 Alt=2

==== * * * Top of File * * *
==== /* This is my PROFILE XEDIT */
      |...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...8...+...9...+...10...+...11...+...12...+
==== * * * End of File * * *

====> i_

XEDIT 1 File

4B 00:00.1 26/008
```

Leave input by hitting ENTER on null line

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=11 Line=1 Col=1 Alt=0
DMSXMD573I Input mode:
```

```
* * * Top of File * * *
/* This is my PROFILE XEDIT */
|...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...8...+...9...+...10...+...11...+...12...+...13.
'SET CASE MIXED IGNORE' /* Allow upper/lower case */
'SET STAY ON' /* Don't move if I don't find something */
'SET WRAP ON' /* If I reach EOF, start again at the top */
'SET SCALE OFF' /* I don't like the scale */
'SET PREFIX ON' /* Prefix area on the Left */
'SET CMDLINE ON' /* Large input area on the bottom */_
```

```
====> * * * Input Zone * * *
```

Input-mode 1 File

4B

:00.1

21/070

CASE

- CASE UPPER|MIXED RESPECT|IGNORE
 - Entry:
 - UPPER translates everything typed to uppercase
 - MIXED means just the way you type it
 - Search
 - RESPECT for searches, has to match exactly
 - IGNORE matches regardless of case
 - CASE MIXED IGNORE
 - /Airplane will locate:
 - » AIRPLANE ← UPPER RESPECT locates this one
 - » Airplane ← MIXED RESPECT locates this one
 - » airplane
 - » airPlane

STAY and WRAP

- SET STAY ON|OFF
 - On = keep CURLINE if not found
- SET WRAP ON|OFF
 - On = search to EOF, then go to top and search to CURLINE

CURLINE, CMDLINE, SCALE, TABLINE and PREFIX

- CURLINE ON M+/-|n+/-
 - Current line pointer.
 - M is middle, Mn or M+n is middle plus n lines, - is above middle
 - +n, or just n, is lines from top, -n is lines from bottom
- CMDLINE ON|TOP|BOTTOM
 - ON two lines at bottom of screen for commands
 - TOP one line on line 2
 - BOTTOM one line at bottom of screen
- SCALE OFF|ON M+/1|n+/-
- TABLINE OFF|ON M+/-|n+/-
- PREFIX OFF|ON LEFT|RIGHT
 - NUMS OFF|ON

This is what we look like so far

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=8 Line=0 Col=1 Alt=9
```

```
==== * * * Top of File * * *
==== /* This is my PROFILE XEDIT */
==== 'SET CASE MIXED IGNORE'
==== 'SET STAY ON'
==== 'SET WRAP ON'
==== 'SET SCALE OFF'
==== 'SET PREFIX ON'
==== 'SET CMDLINE ON'
==== 'SET CURLINE ON 10'
==== * * * End of File * * *
```


```
====> q pf_
```

XEDIT 1 File

4B

:00.1

26/011



```
PF1    BEFORE  HELP MENU
PF2    BEFORE  SOS LINEADD
PF3    BEFORE  QUIT
PF4    BEFORE  TABKEY
PF5    BEFORE  SCHANGE 6
PF6    ONLY   ?
PF7    BEFORE  BACKWARD
PF8    BEFORE  FORWARD
PF9    ONLY   =
PF10   BEFORE  RGTLEFT
PF11   BEFORE  SPLTJOIN
PF12   BEFORE  CURSOR HOME
PF13   BEFORE  HELP MENU
PF14   BEFORE  SOS LINEADD
PF15   BEFORE  QUIT
PF16   BEFORE  TABKEY
PF17   BEFORE  SCHANGE 18
PF18   ONLY   ?
PF19   BEFORE  BACKWARD
PF20   BEFORE  FORWARD
PF21   ONLY   =
PF22   BEFORE  RGTLEFT
PF23   BEFORE  SPLTJOIN
PF24   BEFORE  CURSOR HOME
```

4B

@:00.1

26/001

MORE... DVFVM

PF3 is QUIT! What if??

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=8 Line=0 Col=1 Alt=9  
DMSXSU577E File has been changed; type QQUIT to quit anyway
```

```
==== * * * Top of File * * *  
==== /* This is my PROFILE XEDIT */  
==== 'SET CASE MIXED IGNORE'  
==== 'SET STAY ON'  
==== 'SET WRAP ON'  
==== 'SET SCALE OFF'  
==== 'SET PREFIX ON'  
==== 'SET CMDLINE ON'  
==== 'SET CURLINE ON 10'  
==== * * * End of File * * *
```

```
====> _
```


XEDIT 1 File

4B

@:00.1

26/007

Adding some color



SHARE
Educate • Network • Influence

```
>> -SET- -COLOR- *
      (1) (2) (2)
      |-----|-----|-----|
      | -Arrow--- | -Blue--- | -BLInk--- |
      | -Cmdline-- | -Red---- | -REVvideo-- |
      | -Curline-- | -Pink--- | -Underline- |
      | -Filearea- | -Green--- | -NONE----- |
      | -Idle---  | -Turquoise- |
      | -Msgline-- | -Yellow--- |
      | -Pending-- | -white---- |
      | -PRefix--- | -Default--- |
      | -Scale---- |
      | -SHadow--- |
      | -STatarea- |
      | -Tabline-- |
      | -TOfeof--- |
```

Complete your session evaluations online at www.SHARE.org/Orlando-Eval

Better, but more to do

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=15 Line=6 Col=1 Alt=0
```

```
==== * * * Top of File * * *
==== /* This is my PROFILE XEDIT */
==== 'SET CASE MIXED IGNORE' /* Allow upper/lower case */
==== 'SET STAY ON' /* Don't move if I don't find something */
==== 'SET WRAP ON' /* If I reach EOF, start again at the top */
==== 'SET SCALE OFF' /* I don't like the scale */
==== 'SET PREFIX ON' /* Prefix area on the left */
==== 'SET CMDLINE ON' /* Large input area on the bottom */
==== 'SET CURLINE ON 10' /* Place current line on screen line 10 */
==== 'SET COLOR TOFEOF PINK'
==== 'SET COLOR CURLINE YELLOW HIGH'
==== 'SET COLOR SCAL TURQ NOHIGH'
==== 'SET COLOR PREFIX TURQ NOHIGH'
==== 'SET COLOR IDLINE WHITE NOHIGH'
==== 'SET COLOR CMDLINE WHITE'
==== 'SET COLOR MSGLINE RED HIGH'
==== * * * End of File * * *
```

```
====> _
```

```
XEDIT 1 File
```

```
4B
```

```
@:00.1
```

```
26/007
```

A look at the screen

```
PROFILE XEDIT A1 V 255 Trunc=255 Size=15 Line=6 Col=1 Alt=0 ← Idline
DMSXDC546E Target not found ← Msgline

==== * * * Top of File * * * ← TOfeof
==== /* This is my PROFILE XEDIT */
==== 'SET CASE MIXED IGNORE' /* Allow upper/lower case */
C ← 'SET STAY ON' Pending /* Don't move if I don't find something */
==== 'SET WRAP ON' /* If I reach EOF, start again at the top */
==== 'SET SCALE OFF' /* I don't like the scale */
==== 'SET PREFIX ON' /* Prefix area on the left */ ← Curline
==== ----- 2 line(s) not displayed ----- ← SHadow
==== 'SET COLOR TOFEOF PINK'
==== 'SET COLOR CURLINE YELLOW HIGH' ← Scale
==== 'SET COLOR SCAL TURQ NOHIGH'
|...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...8...+...9...+...10...+...11...+...12...+
==== 'SET COLOR PREFIX TURQ NOHIGH'
==== 'SET COLOR IDLINE WHITE NOHIGH' ← Filearea
==== 'SET COLOR CMDLINE WHITE'
==== 'SET COLOR MSGLINE RED HIGH'
==== * * * End of File * * *
Arrow
PRfix
Tabline
STatarea
====> /FRED ← Cmdline
C pending...
```

Prefix

- . name Set a symbolic name
- < or > Shift left or right
- / Move to Curline
- “ Duplicate
- C Copy
- D Delete
- E Extend (works where line > screen width)
- F Following
- I Insert
- M Move
- P Preceding
- S Show
- X eXclude
- SCALE Put scale on here
- SI Structured Input mode (lines up with previous line)
- TABL Put Tabline on here

More on Prefix

- Numbers may be included with command
 - C15 Copies next 15 lines
- Commands can be blocked: >>, <<, CC, DD, MM, XX
 - CC on two lines copies everything between

```
==== 'SET CASE MIXED IGNORE' /* Allow upper/lower case */
CC=== 'SET STAY ON' /* Don't move if I don't find something */
==== 'SET WRAP ON' /* If I reach EOF, start again at the top */
==== 'SET SCALE OFF' /* I don't like the scale */
CC=== 'SET PREFIX ON' /* Prefix area on the left */
==== 'SET CMDLINE ON' /* Large input area on the bottom */
==== 'SET CURLINE ON 10' /* Place current line on screen line 10 */
```

- >>4 indents all the lines between >> 4 columns

```
==== 'SET CURLINE ON 10' /* Place current line on screen line 10 */
=>>4= 'SET COLOR TOFEOF PINK'
==== 'SET COLOR CURLINE YELLOW HIGH'
==== 'SET COLOR SCAL TURQ NOHIGH'
==== 'SET COLOR PREFIX TURQ NOHIGH'
>>==== 'SET COLOR IDLINE WHITE NOHIGH'
==== 'SET COLOR CMDLINE WHITE'
```

- On CMDLINE: RESET. Clears any pending, does not clear .name

Location, location, location

- :n Go to a specific line
- Nx or x Move down x lines
- Ux or -x Move up x lines
- PF7 Move up a screen
- PF8 Move down a screen

- TOP Go to top of file
- Bottom Go to bottom of file

- /string Go locate next occurrence of string
- -/string Go locate previous occurrence of string
- ^/string Locate a line without string

- Find string String starts in Column 1
- NFind string Line doesn't have string in Column 1
- FUp or FINDUp Toward the Top

What else can effect locate

- SET VARBLANK OFF|ON
 - Allows string to have multiple blanks
 - /air plane locates air plane and air plane
- SET SPILL OFF|ON
 - Allows words in string to be split across lines
- SET ARBCHAR OFF|ON char
 - Arbchar is like a wildcard in string
 - ARBCHAR ON \$
 - /air\$plane locates airplane, air plane, or air in plane
- SET ZONE 1|zone1 *|zone2
 - Restricts searches to items within the zone
- PRESERVE/RESTORE
 - PRESERVE Saves settings like ZONE, TABS, ARBCHAR etc.
 - RESTORE brings them back to what they were

ALL

- All works like locate but display all lines in file with string
 - ALL /string/ Only displays lines containing string
 - ALL Displays all lines
- SHADOW ON shows: -- x line(s) -- not displayed
- Easy to find specific subdata
- SET SCOPE DISPLAY|ALL
 - ALL means changes hit all lines displayed or not

Range

- Limit the activity to within the defined range (except FILE/SAVE)
- SET RANge target1 target2
 - Target can be:
 - Absolute :x
 - Relative n or -n
 - Name .name
 - String -/string/ or /string/
- Default is :1 *

RANGE -/scal/ /scal/

PROFILE XEDIT A1 V 255 Trunc=255 Size=15 Line=8 Col=1 Alt=0

```
==== * * * Top of Range (Line=5) * * *
==== 'SET SCALE OFF'
==== 'SET PREFIX ON'
==== 'SET CMDLINE ON'
==== 'SET CURLINE ON 10'
==== 'SET COLOR TOEOF PINK'
==== 'SET COLOR CURLINE YELLOW HIGH'
==== 'SET COLOR SCAL TURQ NOHIGH'
==== * * * End of Range (Line=11) * * *
```

====> _

XEDIT 1 file

AB

@:00.1

26/007

Change and Alter

- Change /string/newstring/ lines|1 occurrences|1 relative_position|1
 - Delimiter does not have to be a /
 - Lines can be # of lines, string, or .name
 - c/FRED/BARNEY/* * change all lines all occurrences
 - c/FRED/BARNEY/1 3 3 change this line 3 times starting with 3rd FRED
- ALter char1 newchar lines occurrences relative_position
 - Use for changing hex codes
 - Char1 and/or newchar can be 2-digit hex code
 - AL 5C 05
 - AL * \$

Why Change and Alter are important

```
TEST FILE A1 V 80 Trunc=80 Size=7 Line=3 Col=1 Alt=2

==== * * * Top of File * * *
==== z1a001 z1a003
==== z1b002";
==== c1b00";
==== z1b002";
==== z1b026 z1xc9124
==== z1b046 z1xc9134 z1a015
==== z1b021
==== * * * End of File * * *

====> _

XEDIT 1 File

4B @:00.1 26/007
```


Verify

- Verify [Hex] start_col end_col ...
 - Up to 28 pairs can be specified
 - Columns can be repeated
 - Can be in any order
 - V 1 8 20 27 60 66 1 8

Right/Left

- Not to be confused with SHIFT which moves data
- Right n Shift view n columns right
- Left n Shift view n columns left
- PF10 RGTLEFT

```
V$BLDSYS FIELDS E1 V 241 Trunc=241 Size=21 Line=7 Col=1 Alt=0
```

```
==== * * * Top of File * * *
```

```
==== * This file contains the variable details for BUILDSYS and LNXNAMES
```

```
==== * mtrx=Titles in the Linux Matrix spreadsheet on Sharepoint
```

```
==== * ttls=Titles on the screen
```

```
==== * flds=tags in the LINUX NAMES File
```

```
==== * pos=Row,column on the screen
```

```
==== * len=field length
```

```
==== * prot=Protected field, N means data can be entered or changed.
```

```
==== * form=Format of the field, U=upper case, M=Mixed case, I=Ip address, N=Number, YN=Yes/No
```

```
==== * req=Required field. won't save unless value specified if set to Y
```

```
==== * dup=Fields to use when creating duplicates of the current build
```

```
==== * startup_list are valid values for start_up
```

```
|...+...1...+...2...+...3...+...4...+...5...+...6...+...7...+...8...+...9...+...10...+...11...+...12...+
==== udscreen_mtrx 'Hostname Other_DNS_names IP_Address . Gateway VLAN LAN NIC NICname Layer2 BCP_Hostname BCP_Full_Domain_Name
BCP_IP BCP_Gateway Monitor Backup zVM_LPAR Startup OS Contact Group_Email Function . .
==== udscreen_ttls 'Hostname Full_Domain_Name IP Netmask Gateway VLAN LAN NIC NICname Layer2 BCP_Hostname BCP_Full_Domain_Name
BCP_IP BCP_Gateway Monitor Backup Run_on_System Startup OS_Level Contact Group_Email Function P2K_Group Vel_Class'
==== udscreen_flds 'hostname fqdn ip netmask gateway vlan lan nic nicname layer2 bcp_hostname bcp_fqdn
bcp_ip bcp_gateway monitor backup runsys startup os_level contact grp_email function p2kgrp veluclass'
==== udscreen_pos '7.2 8.2 9.2 9.25 9.54 10.25 10.2 11.2 11.25 10.54 18.2 19.2
20.2 20.42 12.2 12.25 13.2 12.54 7.52 14.2 15.2 16.2 13.30 11.54'
==== udscreen_len '20 35 15 15 15 4 8 4 4 3 20 35
15 15 3 3 6 6 12 40 25 64 35 8'
====> v 1 125_
```

```
X E D I T 1 File
```

```
@B
```

```
@:00.1
```

```
26/014
```

PF10 RGTLEFT

```
V$BLSYS FIELDS  E1  V 241  Trunc=241 Size=21 Line=7 Col=1 Alt=0
```

```
==== * * * Top of File * * *
```

```
==== * This file contains the variable details for BUILDSYS and LNXNAMES
```

```
==== * mtrx=Titles in the Linux Matrix spreadsheet on Sharepoint
```

```
==== * ttls=Titles on the screen
```

```
==== * flds=tags in the LINUX NAMES File
```

```
==== * pos=Row.column on the screen
```

```
==== * len=field length
```

```
==== * prot=Protected field, N means data can be entered or changed.
```

```
==== * form=Format of the field, U=upper case, M=Mixed case, I=Ip address, N=Number, YN=Yes/No
```

```
==== * req=Required field. Won't save unless value specified if set to Y
```

```
==== * dup=Fields to use when creating duplicates of the current build
```

```
==== * startup_list are valid values for start_up
```

```
|...+....1....+....2....+....3....+....4....+....5....+....6....+....7....+....8....+....9....+...10....+...11....+...12....+
```

```
==== udscreen_mtrx 'Hostname Other_DNS_names IP_Address . Gateway VLAN LAN NIC NICname Layer2 BCP_Hostname BCP_Full_Domain_Nam
```

```
==== udscreen_ttls 'Hostname Full_Domain_Name IP Netmask Gateway VLAN LAN NIC NICname Layer2 BCP_Hostname BCP_Full_Domain_Nam
```

```
==== udscreen_flds 'hostname fqdn ip netmask gateway vlan lan nic nicname layer2 bcp_hostname bcp_fqdn
```

```
==== udscreen_pos '7.2 8.2 9.2 9.25 9.54 10.25 10.2 11.2 11.25 10.54 18.2 19.2
```

```
==== udscreen_len '20 35 15 15 15 4 8 4 4 3 20 35
```

```
==== udscreen_prot 'N Y Y Y Y N N Y Y Y N Y
```

```
==== udscreen_req 'Y Y Y Y Y Y Y Y Y Y Y Y
```

```
==== udscreen_form 'M M I I I N U N U YN M M
```

```
==== udscreen_dup '1.55 N *.15 N N N N N N N 2.55 N
```

```
==== startup_list 'EARLY NORMAL LATE NO'
```

```
====> _
```

```
X E D I T 1 File
```

```
4B
```

```
:00.1
```

```
26/007
```

PF10 again moves back

```
V$BLDSYS FIELDS  E1  V 241  Trunc=241 Size=21 Line=7 Col=1 Alt=0

===== * * * Top of File * * *
=====
=====
=====
=====
=====
=====
=====
=====
=====
=====
=====
+. . . 10 . . . +. . . 11 . . . +. . . 12 . . . +. . . 13 . . . +. . . 14 . . . +. . . 15 . . . +. . . 16 . . . +. . . 17 . . . +. . . 18 . . . +. . . 19 . . . +. . . 20 . . . +. . . 21 . . . +. . .
===== BCP_Hostname BCP_Full_Domain_Name BCP_IP BCP_Gateway Monitor Backup zVM_LPAR Startup OS Contact Group_Email Functi
===== BCP_Hostname BCP_Full_Domain_Name BCP_IP BCP_Gateway Monitor Backup Run_on_System Startup OS_Level Contact Group_Email Functi
===== bcp_hostname bcp_fqdn bcp_ip bcp_gateway monitor backup runsys startup os_level contact grp_email functi
===== 18.2 19.2 20.2 20.42 12.2 12.25 13.2 12.54 7.52 14.2 15.2 16.2
===== 20 35 15 15 3 3 6 6 12 40 25 64
===== N Y Y Y N N N N N N N N
===== Y Y Y Y N N N Y N N N
===== M M I I YN YN R S U M M M
===== 2.55 N N N N 1.40 N N N N N
=====
=====
=====> _
```

X E D I T 1 File

4B 00.1 26/007

RIGHT 100

```
V$BLSYS_FIELDS E1 V 241 Trunc=241 Size=21 Line=13 Col=1 Alt=0
```

```
====  
====  
====  
====  
====  
.....11.....12.....13.....14.....15.....16.....17.....18.....19.....20.....21.....22.....+  
==== tname BCP_Full_Domain_Name BCP_IP BCP_Gateway Monitor Backup zvm_LPAR Startup OS Contact Group_Email Function .  
==== tname BCP_Full_Domain_Name BCP_IP BCP_Gateway Monitor Backup Run_on_System Startup OS_Level Contact Group_Email Function P2K_  
==== tname bcp_fqdn bcp_ip bcp_gateway monitor backup runsys startup os_level contact grp_email function p2kg  
==== 19.2 20.2 20.42 12.2 12.25 13.2 12.54 7.52 14.2 15.2 16.2 13.3  
==== 35 15 15 3 3 6 6 12 40 25 64 35  
==== Y Y Y N N N N N N N N N  
==== Y Y Y N N N N Y N N N N  
==== M I I YN YN R S U M M M M  
==== N N N N N 1.40 N N N N N N  
====  
==== * * * End of File * * *
```

```
====> right 100_
```

XEDIT 1 File

4B

@:00.1

26/016

```
V$BLDSYS FIELDS  E1 V 241 Trunc=241 Size=21 Line=13 Col=1 Alt=0
Total offset exceeds LRECL (241)
```

```
====
====
====
====
====
.....21.....22.....23.....24>.....25.....26.....27.....28.....29.....30.....31.....32.....+
==== Group_Email Function .
==== Group_Email Function P2K_Group vel_Class'
==== grp_email function p2kgrp veluclass'
==== 15.2 16.2 13.30 11.54'
==== 25 64 35 8'
==== N N N N'
==== N N N N'
==== M M M V'
==== N N N N'
====
==== * * * End of File * * *
```

```
====> left 200
```

```
XEDIT 1 file
```

```
4B
```

```
@:00.1
```

```
26/013
```


Pieces

- PUT n fn ft fm
 - Copy lines to a different file
 - Appends to end if file exists
- PUTD n fn ft fm
 - Same as PUT except Delete lines after copying
- GET fn ft fm firstrec number_of_recs
 - Pull a copy of records at curline

Multiple file

- XEDIT fn|= ft|= fm|=
- Q RING
 - DMSXQR530I 2 file(s) in storage
 - USER DISKMAP A1 F 100 Trunc=100 Size=705 Line=508 Col=1 Alt=0
 - USER DIRECT C1 F 80 Trunc=72 Size=4743 Line=4740 Col=1 Alt=0
- SCREEN n Horizontal|Vertical
 - Split into 2 or more screens
 - Can define up to 16 screens with SCREEN DEFINE

```

USER      DISKMAP  A1  F 100  Trunc=100 Size=705 Line=508 Co|=1 Alt=0

00508 VHPP01  VMANAGER  0191  3390  00001  00005  00005  *
00509      VMANAGER  051D  3390  00006  00010  00005  *
00510      VMANAGER  0193  3390  00011  00025  00015  *
00511      VMANAGER  0195  3390  00026  00040  00015  *
00512      VMANAGER  01FF  3390  00041  00045  00005  *
00513      ZVMN012A  02C4  3390  00046  00046  00001  *
00514      ZVMN012A  02A6  3390  00047  00047  00001  *
00515      ZVMN012A  02A2  3390  00048  00048  00001  *
00516      49 49 1 GAP
00517      ZVMN012A  0210  3390  00050  00064  00015  *
====>
USER      DIRECT  C1  F 80  Trunc=72 Size=4743 Line=4741 Co|=1 Alt=0

===== USER CMS1      WD5JU8QP  32M  64M G
===== INCLUDE IBMDFLT
===== AUTOLOG AUTOLOG1 OP1 MAINT
===== ACCOUNT ACT4 CMSTST
===== MACH ESA
===== IPL 190
===== *
===== *****
===== *
===== MDISK 191 3390 49 1 VHPP01 MR
====> _

X E D I T  2 Files

```

Column commands

- CAppend string Add to the end on the line
- CDelete x Deletes x number of characters
- CFirst Put column pointer in col 1
- CInsert string Insert string at column pointer
- CLAst Move column pointer to end of zone
- CLocate ?? Move column pointer to ...
 - could be an absolute column number
 - Relative column number
 - String
 - /string finds first occurrence on a line and goes to next line
 - CL string finds next occurrence, even if on same line

Saving data and leaving the file

- AUTOSAVE n A|mode
 - Save file every n changes. Creates an AUTOSAVE file that can be used to recover if terminal session gets terminated or lost. QUIT leaves AUTOSAVE file intact. FILE or SAVE erases AUTOSAVE FILE.
- SAVE fn ft fm
 - Save data to disk, reset ALT=0
- SSAVE fn ft fm
 - If fileid was changed or file exists, replace file.
- FILE fn ft fm
 - Save the file and QUIT
- FFILE
 - If fileid was changed to an existing file, replace file and quit
- QUIT
 - Leave file.
- QQUIT
 - Leave file without saving even if changes were made.

EXECs

- Three types of EXEC languages
 - EXEC &CONTROL OFF (default)
 - EXEC2 &TRACE OFF
 - REXX /* */

A split screen exec

```
/* Assign to PF2, when PF2 hit splits at that location */
/* If past column 20, splits vertically. On cmdline reset to 1 screen */
'COMMAND EXTRACT /CURSOR/SCREEN/CMDLINE/LSCREEN/PREFIX'
if cmdline.2 = cursor.1 then do
  'COMMAND SCREEN 1'
  exit
end
scrn_hgt = lscreen.5
scrn_wth = lscreen.6
v_split = 20
if (prefix.1 = 'ON' & prefix.2 = 'LEFT') then v_split = 26
if cursor.2 > v_split then do
  if lscreen.4 /= 1 then cursor.2 = cursor.2 + lscreen.4 - 1
  scrn_wth1 = cursor.2 - 1
  scrn_sth2 = scrn_wth - cursor.2 + 1
  'COMMAND SCREEN WIDTH' scrn_wth1 scrn_wth2
  exit
end
else do
  if lscreen.3 /= 1 then cursor.1 = cursor.1 + lscreen.3 - 1
  scrn_hgt1 = cursor.1 - 1
  scrn_hgt2 = scrn_hgt - cursor.1 + 1
  'COMMAND SCREEN SIZE' scrn_hgt1 scrn_hgt2
  exit
end
```

SPLSCR in action

```
PROFILE XEDIT B1 V 255 Trunc=255 Size=36 Line=0 Col=1 Alt=0
```

```
==== * * * Top of File * * *
==== 7* Standard profile for XEDIT on my account. */
==== 'SET MSGMODE OFF'
==== 'CMSEEDIT ON'
==== 'SET SCAL OFF'
==== 'SET CASE MIXED IGNORE'
==== 'SET STAY ON'
==== 'SET SHADOW OFF'
==== 'SET CURLINE ON 10'
==== 'SET MSGMODE ON'
==== 'SET WRAP ON'
==== 'SET COLOR TOFE0F PINK'
==== 'SET COLOR CURLINE YELLOW HIGH'
==== 'SET COLOR SCAL TURQ NOHIGH'
==== 'SET COLOR PREFIX TURQ NOHIGH'
==== 'SET COLOR IDLINE WHITE NOHIGH'
====>
```

```
XEDIT 1 File
```

```
4B
```

```
:00.1
```

```
10/007
```


Go from horizontal to vertical

```
PROFILE XEDIT B1 V 255 Trunc=255 Size=36 Line=0 Col=1 Alt=0
```

```
==== * * * Top of File * * *
==== /* Standard profile for XEDIT on my account. */
==== 'SET MSGMODE OFF'
====>
```

XEDIT 1 File

```
PROFILE XEDIT B1 V 255 Trunc=255 Size=36 Line=0 Col=1 Alt=0
```

```
==== * * * Top of File * * *
==== /* Standard profile for XEDIT on my account. */
==== 'SET MSGMODE OFF'
==== 'CMSEEDIT ON'
==== 'SET SCAL OFF'
==== 'SET CASE MIXED IGNORE'
==== 'SET STAY ON'
====>
```

XEDIT 1 File



00:00.2

12/055

PROFILE XEDIT B1 V 255 Trunc=255 Size=36 Line=0 PROFILE XEDIT B1 V 255 Trunc=255 Size=36 Line=0 Col=1 Alt=0

```
==== * * * Top of File * * *
==== /* Standard profile for XEDIT on my account. */
==== 'SET MSGMODE OFF'
==== 'CMSEDIT ON'
==== 'SET SCAL OFF'
==== 'SET CASE MIXED IGNORE'
==== 'SET STAY ON'
==== 'SET SHADOW OFF'
==== 'SET CURLINE ON 10'
==== 'SET MSGMODE ON'
==== 'SET WRAP ON'
==== 'SET COLOR TOFEOF PINK'
==== 'SET COLOR CURLINE YELLOW HIGH'
==== 'SET COLOR SCAL TURQ NOHIGH'
==== 'SET COLOR PREFIX TURQ NOHIGH'
==== 'SET COLOR IDLINE WHITE NOHIGH'
==== 'SET COLOR CMDLINE WHITE'
====> _
```

4B

:00.1

27/007

Show the PF keys on the screen

```
/* Display PF keys on the screen */
'COMMAND EXTRACT /CMDLINE/LSCREEN/PF*/RESERVED/COLOR SCALE/'
select
  when cmdline.1 = 'ON' then pflin1 = lscreen.1 - 3
  when cmdline.1 = 'BOTTOM' then pflin1 = lscreen.1 - 2
  otherwise pflin1 = lscreen.1 - 1
end
pflin2 = pflin1 + 1
if reserved.0 > 0 & word(reserved.1,1) = pflin1 then do
  'COMMAND SET RESERVED' pflin1 'OFF'
  'COMMAND SET RESERVED' pflin2 'OFF'
end
pl = ((lscreen.2 -36) + 1) % 6 /* 6 PFxx=/line and a blank on 5 */
pflin1t = 'PF1= 'left(pf1.2,pl) 'PF2= 'left(pf2.2,pl) 'PF3= 'left(pf3.2,pl) ,
  'PF4= 'left(pf4.2,pl) 'PF5= 'left(pf5.2,pl) 'PF6= 'left(pf6.2,pl)
'COMMAND SET RESERVED' pflin1 color.1 'NONE PS0' color.3 pflin1t
pflin2t = 'PF7= 'left(pf7.2,pl) 'PF8= 'left(pf8.2,pl) 'PF9= 'left(pf9.2,pl) ,
  'PF10='left(pf10.2,pl) 'PF11='left(pf11.2,pl) 'PF12='left(pf12.2,pl)
'COMMAND SET RESERVED' pflin2 color.1 'NONE PS0' color.3 pflin2t
exit
```

How it looks on a mod-5

```
PROFILE XEDIT B1 v 255 Trunc=255 Size=36 Line=0 Col=1 Alt=0
```

```
==== * * * Top of File * * *
==== /* Standard profile for XEDIT on my account. */
==== 'SET MSGMODE OFF'
==== 'CMSEEDIT ON'
==== 'SET SCAL OFF'
==== 'SET CASE MIXED IGNORE'
==== 'SET STAY ON'
==== 'SET SHADOW OFF'
==== 'SET CURLINE ON 10'
==== 'SET MSGMODE ON'
==== 'SET WRAP ON'
==== 'SET COLOR TOFEOF PINK'
==== 'SET COLOR CURLINE YELLOW HIGH'
==== 'SET COLOR SCAL TURQ NOHIGH'
PF1= HELP MENU      PF2= SPLSCR      PF3= QUIT          PF4= TABKEY       PF5= SCHANGE 6    PF6= ?
PF7= BACKWARD      PF8= FORWARD    PF9= =            PF10=RGTLLEFT    PF11=SPLTJOIN    PF12=CURSOR HOME
====> _

XEDIT 1 File

4B  @:00.1 26/007
```

On a mod-2

```
PROFILE XEDIT B1 V 255 Trunc=255 Size=36 Line=0 Col=1 Alt=0
```

```
==== * * * Top of File * * *
==== /* Standard profile for XEDIT on my account. */
==== 'SET MSGMODE OFF'
==== 'CMSEDIT ON'
==== 'SET SCAL OFF'
==== 'SET CASE MIXED IGNORE'
==== 'SET STAY ON'
==== 'SET SHADOW OFF'
==== 'SET CURLINE ON 10'
==== 'SET MSGMODE ON'
==== 'SET WRAP ON'
PF1= HELP ME PF2= SPLSCR PF3= QUIT PF4= TABKEY PF5= SCHANGE PF6= ?
PF7= BACKWAR PF8= FORWARD PF9= = PF10=RGTLFT PF11=SPLTJOI PF12=CURSOR
====> _
```

X E D I T 1 File

4B

:00.2

23/07

PIPES

- PIPE is not part of the nucleus
 - Must specify PIPE
- PIPE returns the highest return code of all stages

From easy to complex

- Easy stuff

```
/* Populate a stem, omit comments */  
'PIPE < V$BLDSYS FIELDS *',  
  '| nfind *',  
  '| stem fields.'
```

```
/* Remove blank lines */
```

```
'PIPE stem Id.',  
  '| locate',  
  '| stem Id.'
```

- More complex

```
/* Compare lists of files on two disks */  
'PIPE (endchar ?) < FILES DISK'fm1 'A',  
  '| c: collate MASTER',  
  '| > FILES ONBOTH A',  
  '?',  
  '< FILES DISK'fm2 'A',  
  '| c:',  
  '| > FILES ON'fm1 'A',  
  '?',  
  'c:',  
  '| > FILES ON'fm2 'A'
```

References

- XEDIT User's Guide
- XEDIT Commands and Macro Reference
- CMS PIPELINES User's Guide
- REXX/VM Reference
- REXX/VM User's Guide
 - Manuals can be found at <http://www.vm.ibm.com/library/>

And don't forget about HELP

(Help Menus can be a great place to start).